



# ENERBOND<sup>®</sup> DW

**DRYWALL ADHESIVE**



- Drywall Adhesive
- Construction Adhesive
- Panel Adhesive
- Easy to Use
- Acoustical Sealant  
STC of 69
- Fewer Nail Pops,  
Call Backs
- Fast Application, Less  
Fatigue Using Foam  
Dispensing Tool

- High yield. One can of EnerBond DW replaces up to 40 quart tubes of traditional adhesive.
- Superior adhesion. Bonds to drywall, masonry, vinyl-faced wallboard, wood or steel studs and other surfaces.
- Use up to 66% less fasteners.
- Can withstand building movement without shearing.
- Helps to prevent loose panels.
- No solvents. Won't melt insulation
- Less mudding labor. Fewer "nail pops." Reduces call backs.
- Approved as drywall adhesive. Meets ASTM C557-93 and CGSB 71.25.
- Meets CA25-4 (Adhesives for Structural Use in the Manufacture of Mobile Homes and Commercial Coaches) and conforms to ASTM E72-80 for rack shearing.

(3 6 2 6)

**1.800.800.FOAM**

[www.polyurethanesystems.com](http://www.polyurethanesystems.com)



**THE DOW CHEMICAL COMPANY**

\* Trademark of The Dow Chemical Company

# ENERBOND<sup>®</sup> DW

DRYWALL ADHESIVE

## More Benefits!

### ■ Wall Test

DAPIA-approved shear wall testing - single and double sided. Test available for most major wall board manufacturers per HUD code.

### ■ Fast Application

EnerBond DW eliminates the cumbersome caulking tool. With the professional application tool, you just pull the trigger and apply adhesive. Stop carpal tunnel injuries.

### ■ Bonds to a Wide Variety of Materials

Bonds to drywall, masonry, vinyl-faced wallboard, wood or steel studs and more.

### ■ Elastic Properties

EnerBond DW will expand and compress with the shifting of structures.

### ■ Long Open Time

EnerBond DW allows drywall or panel to be set in place within 15 minutes.

### ■ Portable

The professional application tool allows for complete portability.

### ■ Independent Lab Tests

- ASTM C557-93 "Adhesives for Fastening Gypsum Wallboard to Wood Framing." CGSB 71.25 "Canadian Drywall Adhesive Standard."
- CA25-4 "Standard for the Evaluation of Adhesives for Structural Use in the Manufacture of Mobile Homes and Commercial Coaches."
- REPORT NO. NER-518: Conforms to BOCA, ICBO and SBCCI.
- Conforms to ASTM E72-80 for rack shearing.
- UL Class 1 rated (Flame spread of 15, smoke developed 20).
- Tested as Acoustical Sealant with STC rating of 69.

### ■ Point-Of-Purchase Display

The P.O.P. consists of a base unit and your choice of five headers. It easily will hold up to 78 cans of product, on graduated shelves, and utilizes a very small 'footprint' area, which will save valuable floor space. The "pop-up" design sets up in just minutes.



• EnerBond DW P.O.P. Display



## OTHER GREAT PRODUCTS...



### ■ EnerFoam<sup>®</sup> – The Professional Foam System

Because of its versatility, the EnerFoam Professional Foam System has established itself as the premier polyurethane foam available to professionals. EnerFoam is ideal for applications including insulation, hole and crack filling, blocking insects, acoustical sealing (STC 69), and is the perfect adhesive for insulating concrete forms. EnerFoam's high yield saves professionals both time and money!

### ■ EnerBond<sup>®</sup> SF – Subfloor Adhesive

EnerBond SF is specially formulated for subfloor and drywall applications. Compatible with lumber, concrete, drywall, masonry and metals, one can of EnerBond SF replaces up to 15 quart tubes of traditional adhesives. This solvent-free adhesive reduces squeaks, withstands temperature extremes, and exceeds all major glued subfloor standards. (ASTM D3498, APA-AFG-01, CGSB 71.26 and CA 25-4).

### ■ EnerBond<sup>®</sup> MH – Manufactured Housing Adhesive

EnerBond MH is a specially formulated adhesive technology for Manufactured Housing and Modular Construction. EnerBond MH helps eliminate squeaks in subfloors and loose panels in drywall applications. The adhesive can be used for both vertical and table applications. EnerBond MH exceeds CA25-4, APA-AFG-01, ASTM D3498, CGSB 71.25 and ASTM C557-93.

### ■ EnerFoam<sup>®</sup> 10 & 16 Pounders

EnerFoam 10 & 16 Pounders are formulated to save energy by sealing windows and doors, stopping drafts, blocking insects and rodents and stopping leaks. These fully paintable foams are tack-free in 10 minutes, can be trimmed in two hours, and bond to wood, concrete, brick and most plastics. EnerFoam 10 & 16 Pounders are dispensed in bead form using the adjustable foam dispenser and make sealing fast, easy and economical.

### ■ EnerFoam<sup>®</sup> II - Two-Component Kit

EnerFoam II is the ideal solution for a professional's large application needs. Perfect for filling large holes and gaps, this two-component, self-controlled, portable kit is dispensed through a spray nozzle. EnerFoam II provides superior insulation for all projects and gives professionals the benefits of being moisture-resistant, paintable and solvent-free.

### ■ Foamitt<sup>™</sup> – The Consumer's Choice

This foam is perfect for homeowners who want to seal up their homes. Foamitt is quick and easy to use, has an 18-month shelf life, an insulation R-value of 4.2, and contains a flame retardant. Foamitt is designed to fill holes, gaps, cracks and to insulate around windows, doors and pipe penetrations.



THE DOW CHEMICAL COMPANY

1881 West Oak Parkway, Marietta, GA 30062

☎ 1.800.800.3626 • www.polyurethanesystems.com