



UCAR™ n-Butyl Propionate

Propanoic Acid, Butyl Ester
Butyl Propanoate



Description

UCAR™ n-butyl propionate is a moderately fast evaporating solvent. Its linear structure contributes to effective viscosity reduction and improves solvent diffusion from coating films.

Physical properties

Molecular Weight	130.19
Relative Evaporation Rate nBuAc=1	0.45
Vapor Pressure at 20°C, mmHg	3.44
Density at 20°C lb/gal	7.30
Specific Gravity at 20/20°C	0.8755
Viscosity at 20°C cP	0.8
Surface Tension	
(dynes/cm at 20°C)	25.3
(dynes/cm at 25°C)	-
Hansen Solubility Parameters, [cal/cm ³] ^{1/2}	
Total	8.4
Non-Polar	7.5
Polar	1.6
Hydrogen Bonding	3.3
Boiling Point, °C at 760mm Hg	144.7
Solubility at 20°C	
%Wt In Water	0.2
%Wt Water in	<0.02
Closed Cup Flash Point °F	100
SARA 313 (see note 1 †)	N
Hazardous Air Pollutant (see note 2 † †)	N
Electrical Resistivity MΩ	>1000

† **Note 1:** Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III Section 313

† † **Note 2:** Hazardous Air Pollutants listed under Title III of the Clean Air Act

Classification/Registry Numbers

CAS Number	590-01-2
EINECS	2096695

(Please see second page)

UCAR™ n-Butyl Propionate

Propanoic Acid, Butyl Ester

Butyl Propanoate

Features

- Non-HAP (Hazardous Air Pollutant) Solvent
- Stronger solvency for high solids coatings
- Proper volatility for high solids coatings and printing inks applications
- Linear structure giving faster diffusion through coating and ink films
- High electrical resistance
- Low odor values
- Good resin solvent
- Possible excellent replacement for Methyl n-Amyl Ketone (MAK) or xylene

Applications

- Automotive refinish
- OEM coatings
- Appliance coatings
- Cleaning fluids
- Enamels
- Lacquers
- Polymerization solvent

How supplied

Region	Packaging	Transport Mode
Europe/Africa	Bulk or Drum	Isotank/Marine Vessel/Tank Truck/Package Truck
Latin America	Bulk or Drum	Tank Truck/Package Truck
North America	Drum	Tank Truck/Railcar

Note: Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

The Dow Chemical Company
Danbury, Connecticut 06817 U.S.A.

In the United States and Canada, Product Information: 1-800-447-4369; Fax: 1-989-832-1465; Technical Support: 1-800-SOLVENT
In Europe: +800 3 694 6367; Toll Phone: +32 3 450 2240; Toll Fax: +32 3 450 2815
In the Pacific: +800 7776 7776; Fax: +800 7779 7779
In Other Global Areas: 1-989-832-1556; Fax: 1-989-832-1465

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

