




n-Butyl Acetate

Acetic Acid, n-Butyl Ester
Butyl Ethanoate



Description

Butyl acetate is a colorless solvent with medium volatility and a characteristic fruity ester odor. It has excellent solvency characteristics for polymers, resins, oils and cellulose nitrate and is miscible with all common organic solvents.

Physical properties

Molecular Weight	116.16
Relative Evaporation Rate nBuAc=1	1
Vapor Pressure at 20°C, mmHg	8
Density at 20°C lb/gal	7.35
Specific Gravity at 20/20°C	0.8826
Viscosity at 20°C cP	0.7
Surface Tension	
(dynes/cm at 20°C)	25.3
(dynes/cm at 25°C)	-
Hansen Solubility Parameters, [cal/cm ³] ^{1/2}	
Total	8.5
Non-Polar	7.7
Polar	1.8
Hydrogen Bonding	3.1
Boiling Point, °C at 760mm Hg	126.2
Solubility at 20°C	
%Wt In Water	0.7
%Wt Water in	1.9
Closed Cup Flash Point °F	84
SARA 313 (see note 1 †)	N
Hazardous Air Pollutant (see note 2 † †)	N

† **Note 1:** Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III Section 313

† † **Note 2:** Hazardous Air Pollutants listed under Title III of the Clean Air Act

Classification/Registry Numbers

CAS Number	123-86-4
EINECS	204-658-1

(Please see second page)

n-Butyl Acetate

Acetic Acid, n-Butyl Ester

Butyl Ethanoate

Features

- Blush resistant
- Medium evaporating
- Limited miscibility in water
- Non-HAP (Hazardous Air Pollutant) Solvent
- Outstanding leveling and gloss characteristics
- Excellent solvent power for resins, polymers, oils and cellulose nitrate
- Miscible with all common organic solvents (alcohols, ketones, aldehydes, glycols, ethers, glycol ethers and aromatic and aliphatic hydrocarbons)
- Low intrinsic viscosity
- Good flow properties

Applications

- Coatings
- Coatings for plastic
- Nail care
- Cosmetic / personal care solvent
- Fragrance solvent
- Extraction solvent
- Leather industry
- Pharmaceuticals
- Cleaners

How supplied

Region	Packaging	Transport Mode
Europe/Africa	Bulk or Drum	Isotank/Marine Vessel/Tank Truck/Package Truck
Latin America	Bulk	Isotank, Marine Vessel Tank Truck & Railcar (Mexico Only)
North America	Bulk	Tank Truck/Railcar/Marine Vessel
Pacific	Bulk or Drum	Marine Vessel/Tank Truck/Package Truck

Note: Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

The Dow Chemical Company
Danbury, Connecticut 06817 U.S.A.

In the United States and Canada, Product Information: 1-800-447-4369; Fax: 1-989-832-1465; Technical Support: 1-800-SOLVENT
In Europe: +800 3 694 6367; Toll Phone: +32 3 450 2240; Toll Fax: +32 3 450 2815
In the Pacific: +800 7776 7776; Fax: +800 7779 7779
In Other Global Areas: 1-989-832-1556; Fax: 1-989-832-1465

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

