



Product Information

VORANOL™ RN 490 Polyol

Description


VORANOL™ RN 490 Polyol is a medium functional polyether polyol, initially developed for the production of rigid polyurethane foams.

VORANOL™ RN 490 Polyol is a general purpose base polyol, designed for various rigid foam applications, such as continuous lamination, rigid block production, (dis-) continuous panel production and pipe insulation, but also for other applications such as adhesive, sealant, coating and elastomer applications.

VORANOL™ RN 490 Polyol is suitable for the production of rigid foam using the prepolymer technology

Typical Properties

Properties	Units	Limits	Test Methods
Appearance / physical state		Yellow to brown colored viscous liquid	
Hydroxyl number	mg KOH/g	475–510	ASTM D4274-94d
Water, max.	%	0.100	ASTM E203-96
Color, max.	Gardner	5	ASTM D4890-93
CPR, max.		50	DOWM 101471-SE94A
Specific gravity, 25/25°C		1.100	
Viscosity, 25°C	cSt	5500–6600	ASTM D445-94
Viscosity, 37.8°C	cSt	1600–1900	ASTM D445-94
Flash point, C.O.C.	°C	> 200	



Safety Considerations

Safety Data Sheet [SDS] for VORANOL™ RN 490 Polyol is available from The Dow Chemical Company. SDS is provided to help customers satisfy their own handling, safety and disposal needs, and those that may be required by locally applicable health and safety regulations. SDS sheets are updated regularly. Therefore, please request and review the most current SDS before handling or using any product. Copies of the SDS are available on request through your nearest Dow Sales office.

Toxicity and First Aid

Most VORANOL™ polyols generally present no significant hazard in use when simple precautions are followed. However, some VORANOL™ polyols might present some hazards and before working with these products it is necessary to understand the hazards involved. See SDS for specific information. These polyols are commonly used in «urethane» systems that contain other more hazardous materials (e.g. isocyanates, amines). Anyone working with urethane systems must understand all the hazards involved in handling such systems and must establish and follow safe work procedures. Recommendations for handling, storage, and disposal of each formulation ingredients should be obtained from its supplier.

Skin and Eyes

When working with VORANOL™ polyols, avoid contact of polyol with eyes or skin. Safety glasses are suggested for use with most polyols. However, some VORANOL™ polyols require that chemical workers' goggles be worn. See the product specific SDS, Section 8. Skin contaminated with polyols should be washed with soap and plenty of water. If polyol contacts eyes, flush with plenty of low-pressure flowing water. If irritation occurs from contact with polyols, get prompt medical attention.

Ingestion

If a polyol is swallowed, give large amounts of water to dilute, but never give fluids or induce vomiting if patient is unconscious or is having convulsions. Obtain prompt medical attention.

Inhalation

VORANOL™ polyols when present alone do not present a significant problem from inhalation. If any ill effects should occur, get the affected person to fresh air and obtain prompt medical attention.

Safety Considerations (Cont.)

Fire and Explosion

VORANOL™ polyols are organic materials that will burn under the right conditions of heat and oxygen supply. Store and handle polyols away from open flame or high heat sources. Fires can be extinguished with water fog or other conventional means.

Fire fighters should wear positive pressure, self-contained breathing apparatus.

While polyols have no known explosion limits, if heated to decomposition in a confined area, they may generate sufficient volatile gases to be an explosion hazard. Polyols are stable under normal conditions. Materials to avoid are oxidizing compounds. Hazardous polymerization may occur with isocyanates.

Spills and Disposal

The preferred way of disposal is to incinerate under controlled conditions in accordance with all local and national environmental laws and regulations.

Customer Notice

Dow encourages its customers to review their applications of Dow products from the standpoint of human health and environmental quality. To help ensure that Dow products are not used in ways for which they were not intended or tested, Dow personnel are willing to assist in dealing with ecological and product safety considerations. Your Dow representative can arrange the proper contacts.

Contact:
North America: 1-800-258-2436
Latin America: (+55)-11-5184-8722
Europe: (+800)-3694-6367
Japan: (+800)-7776-7776
Australia: (+800)-7776-7776
www.dow.com

NOTICE: The information and data contained herein do not constitute sales specifications. The product properties may be changed without notice. No liability, warranty or guarantee of product performance is created by this document. It is the Buyer's responsibility to determine whether Dow products are appropriate for Buyer's use and to ensure that Buyer's workplace and disposal practices are in compliance with applicable laws and regulations. No freedom from any patents or other industrial or intellectual property rights is granted or to be inferred.

