


**DOW**


®

# Novel silicone hybrid options for adhesives, molding & underfill


- Enhance mechanical properties of silicones with excellent durability
- Non-yellowing for light module applications
- Tunable technology to fit applications





## UV cure



## Heat cure



## Dual cure



Images: dow\_56231613198, dow\_61864548498  
NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow  
© 2022 The Dow Chemical Company. All rights reserved.  
2000018129

Form No. 11-4274-01-0622 S2D