



Technical Data Sheet


DOWANOL™ DPMA

Synonyms

Dipropylene glycol methyl ether acetate.

Sustainability Attribute:

Chemical Formula



Description

DOWANOL™ DPMA glycol ether provides many of the same properties as DOWANOL™ PMA glycol ether, but with a slower evaporation rate and a lower flammability rating. DOWANOL™ DPMA is rated as a Class III combustible, making it easier to handle, store, and ship. This product is among the lowest viscosity members of the family of DOWANOL™ glycol ethers. The molecule is capped with an acetate group, which reduces its polarity and reduces the solvent's viscosity. The acetate group also eliminates the presence of the reactive hydrogen found in other glycol ethers; thus, DOWANOL™ DPMA glycol ether is an excellent solvent choice for urethanes and other proton-sensitive systems. DOWANOL™ DPMA glycol ether provides excellent active solvency for a very wide range of resin types, including acrylics, epoxies, alkyds, polyesters, and many others.

Uses / Applications

- Active solvent for solvent-based coatings.
- Active solvent for solvent-based silk screen printing inks.
- Tailing solvent for solvent-based coatings

Typical Physical Properties

Property	Unit	Result
Molecular weight	g/mol	190.2
Boiling point @ 760 mmHg, 1.01 ar	°C (°F)	209 (408)
Flash point (Setaflash closed cup)	°C (°F)	87.5 (189.5)
Freezing point	°C (°F)	-25 (-13)
Vapor pressure @ 20°C	mmHg Pa	0.08 10.4
Specific gravity (25/25°C)		0.976
Liquid density @ 20°C	g/cm ³	0.979
@ 25°C	g/cm ³	0.974
Vapor density (air = 1)		6.6

Typical Physical Properties:

This data provided for those properties are typical values, and should not be construed as sales specifications.

Typical Physical Properties (Cont.)

Property	Unit	Result
Viscosity (@ 25°C)	cP or mPa•s	1.7
Surface tension (@ 20°C)	dynes/cm or mN/m	27.3
Specific heat (@ 25°C)	J/g/°C	1.94
Heat of vaporization at normal boiling point	J/g	241
Net heat of combustion — predicted @ 25°C	kJ/g	25.4
Autoignition temperature	°C (°F)	340 (644)

Classification/ Registry Numbers/Country Inventory¹

CAS#	88917-22-0
AICS (Australia)	88917-22-0
DSL (Canada)	88917-22-0
IECSC (China)	88917-22-0
ECI (Korea)	88917-22-0
EINECS (EU)	406-880-6
MITI (Japan)	88917-22-0
ENCS/IHSL (Japan)	2-6-1473
NZIoC (New Zealand)	88917-22-0
PICCS (Philippines)	88917-22-0
TSCA (U.S.)	88917-22-0

¹NOTE: Classifications apply only to this glycol ether product. It is the responsibility of the formulator to ensure that the final finished product complies with the regulations of a given country prior to its sale or distribution in that country.

How Supplied

REGION	PACKAGING	TRANSPORT MODE
Europe/Africa	Drum	Not Applicable
Latin America	Drum	Not Applicable
North America	Bulk/Drum	Tank Truck/Tank Car
Pacific	Bulk/Drum	Tank Truck

Product Stewardship

Dow encourages its customers and potential users to review their applications from the standpoint of human health and environmental aspects. To help ensure that Dow products are not used in ways for which they are not intended or tested, Dow personnel will assist customers in dealing with environmental and product safety considerations. Dow literature, including Material Safety Data Sheets, should be consulted prior to the use.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

