

DOWFAX 20A64 Nonionic Surfactant

General Information

The Dow Chemical Company is a science and technology-based company and one of the world's largest producers of polyalkylene glycols. Our worldwide research, manufacturing, and distribution includes facilities in Europe, North America, Latin America, and Asia-Pacific. With over 30 years experience in polyglycol manufacturing, the industry's broadest product line, and a leadership position in new product development, Dow is uniquely positioned to meet the needs of a diverse global marketplace. This success results from expanding our customers' markets through combined customer formulation knowledge and Dow alkoxylation expertise in joint development applications. Together we focus these resources to help ensure success for our customers and their products.

DOWFAX Nonionic surfactants

DOWFAX* Nonionic Surfactants are high-performance products that feature excellent solvency, low foam characteristics, chemical stability, and a long list of other valuable performance properties. They are produced by polymerizing ethylene oxide (EO), propylene oxide (PO), and/or butylene oxide (BO) in the same molecule. The ratio and order of oxide addition, together with the choice of initiator, control the chemical and physical properties.

DOWFAX 20A64 NONIONIC SURFACTANT —PRODUCT CHARACTERISTICS

DOWFAX 20A64 Nonionic Surfactant is a clear liquid at room temperature with a low pour point. It is an efficient surfactant by having good wetting ability, high degree of surfactancy and low foam characteristic. DOWFAX 20A64 Nonionic Surfactant is readily miscible in water and can be used in combination with other surfactants in a wide variety of aqueous formulations. See Table 1 for Typical Properties of DOWFAX 20A64 Nonionic Surfactant. In addition, DOWFAX 20A64 Nonionic Surfactant is more soluble in cold water than in hot water, if inverse water solubility is required. The optimum operating temperature range for detergency and wetting ability is +/-10°C of the surfactant's cloud point in that system.

Applications and Uses

For high-pressure spray cleaning, DOWFAX 20A64 Nonionic Surfactant offers good wetting characteristics. It is used as a rinse aid and in high performance cleaners for automatic dishwashing units and metal-cleaning operations. DOWFAX 20A64 Nonionic Surfactant complies with EEC directive 82/242/EEC, which governs surfactants use in detergents. DOWFAX 20A64 Nonionic Surfactant is also used in textile processing auxiliaries, household cleaners, metalworking fluids and water treatment for low foam characteristics and wetting ability.

TABLE 1: Typical Properties of DOWFAX 20A64 Nonionic Surfactant

Property (Unit)	Typical Value	Test Method
Viscosity @ 25°C (cSt)	63	ASTM D 445 / D 446
Cloud Point, 1% Aqueous (°C)	31	ASTM D 2024
Cloud Point, 10% Aqueous (°C)	28	ASTM D 2024
Cloud Point, 10% Solvent 1 (°C)	51	ASTM D 2024
Wetting time @ 25°C (sec)	29.4	DIN 53901
Wetting time @ 70°C (sec)	24	DIN 53901
Surface Tension ² (mN/m)	80	ASTM D 1331
Pour Point (°C)	-10	ASTM D 97
Specific Gravity (g/cm³ @ 25°C/25°C)	0.973	ASTM D 892

^{1 10%} surfactant in a solution of 25% diethylene glycol butyl ether in water

Notice: The information and data contained herein do not constitute sales specifications. No liability, warranty or guarantee of final product performance is created by this document.

Technical Expertise When and Where You Need It Dow experts on DOWFAX Nonionic Surfactants are regionally located to quickly respond to your needs. They are globally networked to take maximum advantage of years of combined experience. Whether your question involves products, applications, or regulations, Dow offers comprehensive customer and technical service.

Safe Use and Handling

DOWFAX 20A64 Nonionic Surfactant is easy to store and handle. For specific safe use and handling information, or to obtain a DOWFAX 20A64 Nonionic Surfactant Material Safety Data Sheet, contact your local Dow representative or please visit us at www.dow.com.

Product Stewardship

Dow encourages its customers and potential users of DOWFAX 20A64 Nonionic Surfactant to review their applications from the standpoint of human health and environmental aspects. To help ensure that DOWFAX 20A64 Nonionic Surfactant is not used in ways for which it is not intended or tested, Dow personnel will assist customers in dealing with environmental and product safety considerations. Dow literature, including Safety Data Sheets, should be consulted prior to the use of DOWFAX 20A64 Nonionic Surfactant.

Contact information:

North America: 1-800-447-4369 Europe: (+32) 3-450-2240 Asia/Pacific: (+852) 2879 7339 Other areas: 1-989-832-1556 http://www.dow.com/polyglycols Notice: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



² Temperature 20°C, 1% surfactant in water