



Technical Data Sheet

SYL-OFF™ SL 585 Coating

Solventless silicone release coating for flat release.

Features & Benefits

- Flat release
- Provides stable release
- Formulated with platinum catalyst for ease of handling
- Excellent mist reduction; minimizes mist at high line speeds
- Solventless
- Provides good anchorage to a wide variety of substrates

Applications

- Release coating for pressure sensitive laminate, non stick packaging, and coatings for liners of technical adhesive tapes.
- Release coating for industrial release papers.
- Release coating for high speed die-cutting and label dispensing.

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Form		Liquid
Chemical nature		Reactive siloxane polymer
Appearance		Clear liquid
Active ingredient	%	100
Specific gravity at 25°C (77°F)	g/cm ³	0.98
Viscosity at 25°C (77°F)	cS	110

Description

SYL-OFF™ SL 585 Coating is one component of a multicomponent silicone release coating system.

How to Use

In order to use this product effectively, it must be blended with the appropriate SYL-OFF™ release modifiers, catalysts and crosslinkers. It is recommended that the following formulations be used as a starting point for SYL-OFF™ SL 585 Coating.

Component	Parts by weight		
SYL-OFF™ SL 585 Coating	89.49	89.49	92.68
SYL-OFF™ SL 11 Crosslinker	10.51		
SYL-OFF™ SL 12 Crosslinker		10.51	
SYL-OFF™ 7682-055 Crosslinker			7.32

More detailed information about the use of this SYL-OFF™ material and other SYL-OFF™ materials can be obtained from the Technical Service group.

Food Contact Status

This product may comply with certain FDA, BGvV, Kosher or other regulatory agency requirements for food-contact applications.

Handling Precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life and Storage

When stored at or below 35°C (95°F), in the original unopened containers, this product has a usable life of 24 months from the date of production.

Limitations

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health and Environmental Information

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, dow.com or consult your local Dow representative.

Disposal Considerations

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Technical Representative for more information.

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

