



## SYL-OFF<sup>TM</sup> 2700 Catalyst

#### APPLICATIONS

- Catalyst for release base for pressure sensitive laminate/labelstock.
- Casting papers.
- Industrial release papers.

### TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Form		Liquid
Chemical nature		Organometallic tin catalyst
Appearance		Light yellow
Active ingredient	%	100
Specific gravity at 20°C (68°F)	g/cm <sup>3</sup>	1.15
Flash point, closed cup	°C (°F)	> 93.3 (> 200)

### HANDLING PRECAUTIONS

SYL-OFF<sup>TM</sup> 2700 Catalyst is toxic via skin absorption. Flush contaminated areas with water immediately and obtain medical attention.

Rubber or plastic gloves and safety glasses should be worn when handling this product.

The product is toxic if swallowed and medical attention should be obtained at once. In all cases, if feeling unwell after handling this product, seek medical attention.

PRODUCT SAFETY
INFORMATION REQUIRED FOR
SAFE USE IS NOT INCLUDED IN
THIS DOCUMENT. BEFORE
HANDLING, READ PRODUCT
AND SAFETY DATA SHEETS
AND CONTAINER LABELS FOR
SAFE USE, PHYSICAL AND
HEALTH HAZARD
INFORMATION. THE SAFETY

DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

# USABLE LIFE AND STORAGE

When stored at or above 5°C (40°F) in the original unopened containers, this product has a usable life of 24 months from the date of production.

This material can become solid at room temperature as it has a high freezing point. The material can be gently heated to transition to liquid and can be used without negative impact to product quality or performance. Contact your TS&D representative for questions or more information.

The containers must be stored upright and separated from other chemicals.

# PACKAGING INFORMATION

This product is available in 3.6 kg, 20 kg, and 200 kg containers.

This product is available in 0.5 kg bottles.

### FOOD CONTACT

Coatings formulated with this product are NOT suitable for use in coating applications that eventually involve food contact.

### **LIMITATIONS**

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

### HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

## LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

www.syloff.com



®Trademark of The Dow Chemical Company