



Technical Data Sheet

SYL-OFF™ 7200 Low Release Force Additive

FEATURES & BENEFITS

- Used to decrease the release of cured silicone release film in a controlled manner

APPLICATIONS

- Release additive for pressure sensitive adhesive laminations/label stock
- Non-stick packaging

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications.

| Property | Unit | Result |
|---------------------------------|-------------------|-----------------------|
| Form | | Liquid |
| Chemical Nature | | Non-reactive siloxane |
| Appearance | | Colorless |
| Diluents | | Toluene |
| Active Ingredients | % | 50 |
| Specific Gravity at 25°C (77°F) | g/cm ³ | 0.9 |
| Viscosity at 25°C (77°F) | cSt | 1500 |
| Flash Point, closed cup | °C | 5 |

HOW TO USE

SYL-OFF™ 7200 Low Release Force Additive is an additive to be added into the bath to reduce the release force of the release liner.

HANDLING PRECAUTIONS

SYL-OFF 7200 Additive is flammable. Keep away from heat, sparks and open flames. Use only with adequate ventilation in work and curing areas. Avoid prolonged breathing of vapors.

Direct eye or skin contact may cause slight irritation, which can be relieved by flushing the eye with water for 15 minutes.

Wash hands after handling this product, especially before eating, drinking or smoking.

PRODUCT SAFETY PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

USABLE LIFE AND STORAGE

When stored at or below 32°C (90°F) in the original unopened containers, this product has a usual life of 12 months from the date of production.

PACKAGING INFORMATION

SYL-OFF 7200 Additive is available in pail packaging of 3.4 kg.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

www.syloff.com



®Trademark of The Dow Chemical Company

UNRESTRICTED – May be shared with anyone
®™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
SYL-OFF™ 7200 Low Release Force Additive
© 2017 The Dow Chemical Company. All rights reserved.

Form No. 30-1280-01 A