



## DOWLEX™ NG 2432 UE Polyethylene Resin

### Overview

DOWLEX™ NG 2432 UE Polyethylene Resin for rotational and injection moulding from Dow Plastics is specifically designed for applications requiring stiffness in combination with excellent mechanical properties and good processing. The powder version is named DOWLEX™ NG 2432.10 UE Polyethylene Resin.

Processing and Stabilization: DOWLEX™ NG 2432 UE Polyethylene Resin is fully heat and UV-stabilised resulting in a wide processing latitude, good colour retention and long life expectancy.

Note: DOWLEX™ NG 2432 UE Polyethylene Resin should comply with FDA regulation 177.1520 and with most European food contact regulations when used unmodified and processed according to good manufacturing practices for food contact applications.

#### Applications:

- Large tanks
- IBCs
- Canoes
- Boats

### Additive

- Antiblock: No
- Slip: No
- Processing Aid: No

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Density	0.939 g/cm³	0.939 g/cm³	ISO 1183
Melt Index (190°C/2.16 kg)	3.8 g/10 min	3.8 g/10 min	ISO 1133
Environmental Stress-Cracking Resistance (ESCR)			ASTM D1693
122°F (50°C), 10% AntaroX, Compression Molded	70.0 hr	70.0 hr	
122°F (50°C), 100% AntaroX, Compression Molded	> 1000 hr	> 1000 hr	
Mechanical	Nominal Value (English)	Nominal Value (SI)	Test Method
Tensile Stress			ISO 527-2
Yield, Compression Molded	2760 psi	19.0 MPa	
Yield, Rotational Molded <sup>1</sup>	2610 psi	18.0 MPa	
Break, Compression Molded	1410 psi	9.70 MPa	
Break, Rotational Molded <sup>1</sup>	1170 psi	8.10 MPa	
Tensile Strain			ISO 527-2
Break, Compression Molded	550 %	550 %	
Break, Rotational Molded <sup>1</sup>	500 %	500 %	
Flexural Modulus - 1% Secant (Compression Molded)	106000 psi	730 MPa	ISO 178
Impact	Nominal Value (English)	Nominal Value (SI)	Test Method
Multi-Axial Instrumented Impact Energy			ISO 6603-2
-4°F (-20°C), Rotational Molded <sup>1</sup>	50.9 to 67.9 ft·lb	69.0 to 92.0 J	
-4°F (-20°C), 0.0394 in (1.00 mm), Compression Molded	14.8 ft·lb	20.0 J	
73°F (23°C), Rotational Molded <sup>1</sup>	33.2 to 44.3 ft·lb	45.0 to 60.0 J	
73°F (23°C), 0.0394 in (1.00 mm), Compression Molded	11.1 ft·lb	15.0 J	
Hardness	Nominal Value (English)	Nominal Value (SI)	Test Method
Shore Hardness (Shore D, Compression Molded)	59	59	ISO 868
Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Heat Deflection Temperature			ISO 75-2/B
66 psi (0.45 MPa), Unannealed	149 °F	65.0 °C	

Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Vicat Softening Temperature	253 °F	123 °C	ISO 306/A120
Melting Temperature	262 °F	128 °C	DSC
Peak Crystallization Temperature (DSC)	223 °F	106 °C	DSC

#### Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

<sup>1</sup> 3 to 4 mm plate thickness

## Product Stewardship

The Dow Chemical Company and its subsidiaries ("Dow") has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

## Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

## Medical Applications Policy

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Dow will not knowingly sell or sample any product or service ("Product") into any commercial or developmental application that is intended for:

- long-term or permanent contact with internal bodily fluids or tissues. "Long-term" is contact which exceeds 72 continuous hours;
- use in cardiac prosthetic devices regardless of the length of time involved ("cardiac prosthetic devices" include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices);
- use as a critical component in medical devices that support or sustain human life; or
- use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction.

Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. **DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

## Disclaimer

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications and/or discontinue production; and (4) although Dow may from time to time provide samples of such products, Dow is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

NOTICE: This data is based on information Dow believes to be reliable, as demonstrated in controlled laboratory testing. They are offered in good faith, but without guarantee, as conditions and method of use of Dow products are beyond Dow's control. Dow recommends that the prospective user determine the suitability of these materials and suggestions before adopting them on a commercial scale.

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability for the accuracy and completeness of such information.

## Additional Information

<b>North America</b>		<b>Europe/Middle East</b>	+800-3694-6367
U.S. & Canada:	1-800-441-4369		+31-11567-2626
	1-989-832-1426	Italy:	+800-783-825
Mexico:	+1-800-441-4369		
<b>Latin America</b>		<b>South Africa</b>	+800-99-5078
Argentina:	+54-11-4319-0100		
Brazil:	+55-11-5188-9000		
Colombia:	+57-1-219-6000	<b>Asia Pacific</b>	+800-7776-7776
Mexico:	+52-55-5201-4700		+603-7965-5392

[www.dowplastics.com](http://www.dowplastics.com)

This document is intended for use within Europe

Published: 2005-05-05

© 2019 The Dow Chemical Company

