



CONTINUUM™ DGDC-2490 BK Bimodal Polyethylene Resin

Overview

CONTINUUM™ DGDC-2490 BK Bimodal Polyethylene Resin is produced using UNIPOL™ II process technology. This product may be utilized for pipe applications where long-term hydrostatic strength combined with outstanding resistance to slow crack growth and rapid crack propagation is desired. Suitable applications include natural gas distribution pipes, industrial piping, mining, sewage, and municipal water service lines.

Industrial Standards Compliance:

- ASTM D 3350: cell classification
 - Black Resin - PE445574C CC3 (See NOTES A)
- Plastics Pipe Institute (PPI): TR-4
 - Black Pipe - CONTINUUM™ DGDC-2490 BK Bimodal Polyethylene Resin (See NOTES A)
 - ASTM PE4710 pipe grade
 - 1600 psi HDB and 1000 psi HDS @ 73°F
 - 1000 psi HDB @ 140°F
 - NSF International
 - NSF/ANSI Standard 14
 - NSF/ANS/CAN Standard 61
 - Black Pipe - CONTINUUM™ DGDC-2490 BK Bimodal Polyethylene Resin (See NOTES A)

Consult the regulations for complete details.

NOTES:

- A. Natural resin extruded under proper conditions with carbon black masterbatch DFNF-0092 (6.5%).

Additive

- Antiblock: No
- Slip: No
- Processing aid: Yes

Properties

Physical	Nominal Value	Unit (English)	Nominal Value	Unit (SI)	Test Method ¹
Density					ASTM D792
Black ²	0.960	g/cm ³	0.960	g/cm ³	
Natural	0.950	g/cm ³	0.950	g/cm ³	
Melt Index					ASTM D1238
190°C/2.16 kg	0.081	g/10 min	0.081	g/10 min	
190°C/21.6 kg	7.5	g/10 min	7.5	g/10 min	
Mechanical					
Tensile Strength ³ (Yield)	> 3500	psi	> 24.1	MPa	ASTM D638
Tensile Elongation ³ (Break)	> 500	%	> 500	%	ASTM D638
Flexural Modulus ^{3,4}	150000	psi	1030	MPa	ASTM D790B
Creep Rupture Strength - 1798 psi (12.4 MPa) (68°F (20°C))	> 200	hr	> 200	hr	ISO 1167
Hydrostatic Strength ²					ISO 4427
1798 psi (12.4 MPa) : 68°F (20°C)	> 200	hr	> 200	hr	
725 psi (5.0 MPa) : 176°F (80°C)	> 1000	hr	> 1000	hr	
Resistance to Rapid Crack Propagation, Pc					
Full Scale : 32°F (0°C) ⁵	> 663	psi	> 45.7	bar	ISO 13478
S-4 : 32°F (0°C) ⁶	> 174	psi	> 12.0	bar	ISO 13477
Resistance to Rapid Crack Propagation, Tc					ISO 13477
S-4 @ 10 bar ⁶	< 2	°F	< -17	°C	
Slow Crack Growth PENT ³	10000	hr	10000	hr	ASTM F1473
Impact					
Notched Izod Impact ³ (73°F (23°C))	9.1	ft-lb/in	490	J/m	ASTM D256A
Thermal					
Brittleness Temperature ³	< -103	°F	< -75.0	°C	ASTM D746A
Thermal Stability	> 428	°F	> 220	°C	ASTM D3350

1. ASTM: American Society for Testing and Materials
ISO: International Standardization Organization
2. Natural resin extruded under proper conditions with carbon black masterbatch DFNF-0092 (6.5%).
3. Pipe extruded using natural resins and carbon black masterbatch DFNF-0092 (6.5 wt. %) under proper conditions then compressed into molded parts prepared from pipe according to ASTM D 4703 Procedure C. Properties will vary with changes in molding conditions and aging time. Data generated based on ASTM F1473 at Dow facility. Pent data projected based on representative test samples and conditions.
4. Method I (3 point load)
5. Calculated value, determined by the equation in ISO 4437 based on S-4 test data. Pipe diameter of 10 inch IPS (25.4 cm) and Standard Diameter Ratio (SDR) 11.
6. Pipe diameter of 10 inch IPS (25.4 cm) and Standard Diameter Ratio (SDR) 11.

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Medical Applications Policy

Any and all medical application use of Dow materials, whether a device, a component, or any type of primary or secondary packaging of a medically related object or substance, needs to be reviewed and approved by Dow before any Dow material can be tested in such application.

Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. **DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

For further information contact your Dow sales or technical representative to request a Medical Application Review Request Form.

Additional details of Dow's Medical Applications Policy are available at:
<https://www.dow.com/en-us/support/product-safety.html>

Tobacco and Marijuana Policy

Dow does not support or intend for its products to be used, directly or indirectly, in the production of tobacco, the manufacture of tobacco products, the manufacture and use of electronic cigarettes (including vaping devices), the production of marijuana, or the manufacture of marijuana products intended for human consumption, where the Dow product (or its residues) may be present in the finished product or be alleged to facilitate the delivery of nicotine, other tobacco components, marijuana, or marijuana components.

Harmful Applications Policy

Dow does not intend for its products to be used in applications specifically intended to harm humans.

Contact:

www.dow.com/contact

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications and/or discontinue production; and (4) although Dow may from time to time provide samples of such products, Dow is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

NOTICE: This data is based on information Dow believes to be reliable, as demonstrated in controlled laboratory testing. They are offered in good faith, but without guarantee, as conditions and method of use of Dow products are beyond Dow's control. Dow recommends that the prospective user determine the suitability of these materials and suggestions before adopting them on a commercial scale.

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability for the accuracy and completeness of such information.

For additional information, not covered by the content of this document, contact us via our web site http://www.dow.com/products_services/.

This document is intended for use within North America.

