

SMALL STATIC SHEATHING JOINTS, UP TO 1/8", MAY BE SEALED BY APPLYING SEALANT OVER THE JOINT AND TOOLING IT APPROXIMATELY 1/2" ONTO THE ADJACENT SHEATHING

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING APPLIED OVER SEALANT

DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

SMALL OR LARGE STATIC JOINTS MAY BE FILLED WITH SEALANT AND TOOLED FLUSH TO THE SURFACE

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING APPLIED OVER SEALANT

DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

TO REDUCE THE AMOUNT OF SEALANT USED, A BACKER ROD CAN BE INSERTED INTO JOINTS GREATER THAN 1/4" PRIOR TO APPLYING SEALANT

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING APPLIED OVER SEALANT

DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

SCALE: NTS

USERS OF THIS DESIGN DETAIL OR ILLUSTRATION ACKNOWLEDGE AND AGREE THAT DOW IS NOT PROVIDING ARCHITECTURAL, ENGINEERING OR OTHER PROFESSIONAL SERVICES, AND DOW ASSUMES NO RESPONSIBILITY FOR, AND USERS OF THIS DESIGN DETAIL OR ILLUSTRATION ARE NOT RELYING ON DOW FOR, ANY DESIGN, SPECIFICATIONS, WINDLOAD REQUIREMENTS, MATERIALS, SAMPLES, DESIGN ELEMENTS, OR TESTING OF ANY DESIGN COMPONENTS, INCLUDING THE ADEQUACY OR COMPLETENESS OF THE SAME, SUPPLIED OR USED BY ANY WARRANTY RECIPIENTS OR USERS OF DOW PRODUCTS OR SERVICES. DOW WILL ONLY WARRANT PRODUCTS AS SET FORTH IN A SEPARATE EXECUTED DOW WARRANTY. THIS DESIGN DETAIL OR ILLUSTRATION AND ANY COMMENTS, AND MARK-UPS TO THE DESIGN DETAIL OR ILLUSTRATION, ARE PROVIDED TO SUGGEST HOW DOW PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DESIGN DECISIONS ARE THE RESPONSIBILITY OF THE DESIGNER OF RECORD.

61-8162-01-0224



DOWSIL™ AIR AND WEATHER BARRIER SYSTEM

SHEATHING JOINT TREATMENT METHODS

DRAWING NO.

FW-5

DATE

03/08/2024