



dow.com/submittalsEMEA
dow.com/contactus

IZJAVA O SVOJSTVIMA PROIZVODA

Br. SNF_DOP_018

1. Jedinstveni identifikacijski kod tipa proizvoda:

DOWSIL™ 813C Silikonsko Brtvalo za Građevinarstvo i Betone

2. Broj tipa, šarže ili serijski broj ili neka druga oznaka za identifikaciju građevinskog proizvoda prema članku 11. stavku 4:

Broj šarže: vidi pakiranje

3. Namjena građevinskog proizvoda sukladno primjenljivim harmoniziranim tehničkim specifikacijama, kako je predvidio proizvođač:

Brtvalo za fasadu: EN-15651-1: F-Ext-Int-CC

Brtvalo za ostakljenje: EN-15651-2: G-CC

Brtvalo za pločnike: EN-15651-4:Ext-In-cc

4. Naziv, upisani trgovački naziv ili upisana marka i kontaktna adresa proizvođača prema članku 11. stavku 5:

**Dow Europe GmbH
Bachtobelstrasse 3
8810 Horgen
Switzerland**

5. Ime i prezime te kontaktna adresa predstavnika koji je ovlašten za izvršenje zadataka prema članku 12. stavku 2:

Nije važno

6. Sustavi za procjenu i provjeru postojanosti izvedbe građevinskog proizvoda prema privitku V:

Sustav 3: Sustav 3 za reakciju na požar

7. U slučaju izdavanja izjave o izvedbi određenoga građevinskog proizvoda koji je obuhvaćen harmoniziranom normom:

**EN 15651-1 & EN 15651-2 te reakcija
na požar sustava 3 i izvješće o ispitivanju
by notified body SKZ - Testing GmbH (NB 1213)
Friedrich-Bergius-Ring 22
97076 Würzburg
Germany**

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
© 2018-2022 The Dow Chemical Company. All rights reserved.

29430

Form No. 62-1893-21-0122 S2D



8. U slučaju izdavanja izjave o izvedbi određenoga građevinskog proizvoda za koji je izdana Europska tehnička ocjena:

Nije važno

9. Potvrđena izvedba

Kondicioniranje: Metoda B (prema ISO 8340)
Podloga: Staklo (bez primer-a)
Aluminij (bez primer-a)
Mort M1 (sa DOWSIL™ Construction Primer P)
Mort M2 (bez primer-a)

Ako se na temelju članaka 37. ili 38. primjenjuje Specifična tehnička dokumentacija, proizvod je sukladan sa zahtjevima u nastavku:

Osnovne Karakteristike	Potvrđena Izvedba	Tehnički standard
Reakcija na požar	Klasa E	UNE-EN-ISO 11925-2:2011
Ispuštanje kemikalija	Nema	Vidi sigurnosnotehnički list
Vodonepropusnost i nepropusnost zraka utvrđeni su na temelju:		
Otpor na protok (ISO 7390)	≤ 3 mm	EN 15651-1,2,4
Gubitak volumena (ISO 10563)	≤ 10%	EN 15651-1,2,4
Adhezije/kohezije pri održavanom razvlačenju za negrađevinska brtvila za spojeve u hladnim klimatskim područjima (-30°C) sukladno normi ISO 8339; izmjene i dopune	≤ 0,9 MPa	EN 15651-1,2,4
Adhezije/kohezije pri održavanom razvlačenju za negrađevinska brtvila za spojeve u hladnim klimatskim područjima (-30°C) sukladno normi ISO 8340; izmjene i dopune	Nema nedostataka	EN 15651-1,2,4
Adhezije/kohezije nakon izlaganja toplini, vodi i umjetnom svjetlu sukladno normi ISO 11431	Nema nedostataka	EN 15651-2,4
Elastični povrat (ISO 7389)	≥ 70%	EN 15651-2,4
Izdržljivosti	Zadovoljava	EN 15651-1,2,4

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
© 2018-2022 The Dow Chemical Company. All rights reserved.

29430

Form No. 62-1893-21-0122 S2D



10. Izvedba proizvoda iz točaka 1 i 2 ispunjava potvrđene izvedbe sukladno točki 9. Izjavu o izvedbi na svoju je odgovornost izdao proizvođač naznačen u točki 4.

Ovu je izjavu za proizvođača i u njegovo ime potpisala:

A handwritten signature in black ink, appearing to read "S. Dath", written over a horizontal line.

Sebastien Dath
High Performance Building AETS Manager EMEA
Sebastien.dath@dow.com

Seneffe, 28. siječnja 2022

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
© 2018-2022 The Dow Chemical Company. All rights reserved.

29430

Form No. 62-1893-21-0122 S2D