



dow.com/submittals/EMEA
dow.com/contactus

IZJAVA O LASTNOSTIH

Št. SNF_DOP_018

1. Edinstvena identifikacijska koda za vrsto izdelka:

Gradbeni In Betonski Silikon DOWSIL™ 813C

2. Vrsta, serija ali serijska številka ali kateri koli drug element, ki omogoča identifikacijo gradbenega izdelka skladno s členom 11(4):

Številka serije: glejte embalažo izdelka

3. Predvidena uporaba gradbenih izdelkov skladno z veljavnimi usklajenimi tehničnimi specifikacijami, kot jih je predvidel proizvajalec:

Tesnilna masa za fasade: EN-15651-1: F-EXT-INT-CC

Tesnilna masa za zasteklitve: EN-15651-2: G-CC

Tesnilna masa za tlake: EN-15651: Ext-In-cc

4. Ime, registrirano trgovsko ime ali registrirana blagovna znamka in kontaktni naslov proizvajalca, kot se zahteva skladno s členom 11(5):

**Dow Europe GmbH
Bachtobelstrasse 3
8810 Horgen
Švica**

5. Kjer je potrebno, ime in naslov pooblaščenega zastopnika, čigar naloge so opredeljene v členu 12(2):

Ne velja

6. Sistem ali sistemi ocenjevanja in preverjanja dosledne učinkovitosti gradbenega izdelka, kot je določeno v Prilogi V:

Razred 3: Razred požarne odpornosti 3

7. V primeru izjave o lastnostih gradbenega izdelka, zajetega v usklajenem standardu:

EN 15651-1; EN 15651-2 in razred požarne odpornosti 3 ter izdano poročilo o preskusu

priglašeni organ SKZ - Testing GmbH (NB 1213)

Friedrich-Bergius-Ring 22

97076 Würzburg

Nemčija

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
© 2018-2022 The Dow Chemical Company. All rights reserved.

29430

Form No. 62-1893-28-0122 S2D



8. V primeru izjave o lastnostih gradbenega izdelka, za katerega je bila izdana evropska tehnična ocena:

Ne velja

9. Navedene lastnosti

Pogoji: Priprava B (skladno z ISO 8340)
Substrat: Steklo (brez temeljnega premaza)
Aluminij (brez temeljnega premaza)
Malta M1 (z gradbenim temeljnim premazom DOWSIL™ P)
Malta M2 (brez temeljnega premaza)

Kjer je bila skladno s 37. oziroma 38. členom uporabljena Specifična tehnična dokumentacija, so zahteve, s katerimi je izdelek skladen, naslednje:

Bistvene značilnosti	Navedene lastnosti	Tehnična specifikacija
Odziv na ogenj	Razred E	UNE-EN-ISO 11925-2:2011
Izpusti kemikalij	Brez	Glejte varnostni list izdelka
Vodotesnost in zrakotesnost, kot to določa:		
Odpornost proti pretoku (ISO 7390)	≤ 3 mm	EN 15651-1,2,4
Izguba prostornine (ISO 10563)	$\leq 10\%$	EN 15651-1,2,4
Lastnosti lepljenja/stika pri ohranjanju raztezanja nekonstrukcijskih tesnilnih mas v stikih na hladnih območjih (-30°C) skladno z ISO 8339 s spremembami	≤ 0.9 MPa	EN 15651-1,2,4
Lastnosti lepljenja/stika pri ohranjanju raztezanja nekonstrukcijskih tesnilnih mas v stikih na hladnih območjih (-30°C) skladno z ISO 8340 s spremembami	Brez okvar	EN 15651-1,2,4
Lastnosti lepljenja/stika po izpostavljanju vroči vodi in umetni svetlobi skladno z ISO 11431	Brez okvar	EN 15651-2,4
Elastično okrevanje (ISO 7389)	$\geq 70\%$	EN 15651-2,4
Trpežnost	Prehod	EN 15651-1,2,4

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



10. Učinkovitost izdelka, opredeljena v 1. in 2. točki, je skladna z navedenimi lastnostmi pri 9. točki. Ta izjava o lastnostih se izda na lastno odgovornost proizvajalca, opredeljenega v 4. točki.

Podpisal za in v imenu proizvajalca:

A handwritten signature in black ink, appearing to read "S. Dath", written over a horizontal line.

Sebastien Dath
High Performance Building AETS Manager EMEA
Sebastien.dath@dow.com

Seneffe, 28. januarja 2022

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
© 2018-2022 The Dow Chemical Company. All rights reserved.

29430

Form No. 62-1893-28-0122 S2D