

dow.com/submittalsEMEA dow.com/contactus

DECLARATION OF PERFORMANCE No SNF DOP 033

1. Unique identification code of the product-type:

DOWSIL™ Membrane Dual 0.6

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see product packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 13984:2013: waterproofing and vapor control layer

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Dow Europe GmbH
Bachtobelstrasse 3
8810 Horgen
Switzerland

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 for reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Fire test: MPA Dresden (NB 0767)
Water Tightness & Water vapour transmission:
Kiwa BDA Testing B.V. (NB 0063)

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, The Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Essential Characteristics	Declared Performance	Technical Standard
Reaction to fire	Class E	
Tensile strength (MPa)	≥ 5 MPa	
Elongation at break (%)	≥ 350%	EN 13984:2013
Joint strength (shear): EN 12317-2 (N/50 mm)	≥ 25 N/mm	
Water tightness 2kPa	Pass	
Water vapour properties	μ = 100000	
Resistance to impact	NPD	
Tear resistance (nail shank)	≥ 25 N	
Durability (artificial ageing):		
- Exposure 12 weeks / 70°C EN 1296, EN 1931	Pass	
- Resistance against Alkali EN 1847, EN 12311	Pass	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sebastien Dath

High Performance Building AETS Manager EMEA

Sebastien.dath@dow.com

Seneffe, 28 January 2022