

Treating your unique needs

Get more out of your natural gas operations
with specialty solutions and services

DOW

®



Dow offers one of the broadest product portfolios to remove contaminants from natural gas, allowing us to customize selectivity and efficiently treat gas based on your unique specifications. Our UCARSOL™ Solvents and SELEXOL™ Solvents remove H₂S, CO₂ and trace sulfur and are backed by more than 1,400 references worldwide. Converting an existing amine unit to one of our specialty amine products can help you **reduce energy consumption, increase capacity and reduce maintenance costs.**

Our technical services can help you further optimize performance, from in-house simulation software and pilot plants to analytical reports available in a simple-to-use online platform. Solvent analyses can include:

- Amine concentration
- Acid gas loadings
- Heat-stable salt concentration
- Foaming tendency
- Ion chromatography for heat-stable salt anions
- ICP and atomic absorption metals analyses
- Gas chromatography
- Corrosion monitoring and other specialized analyses



Specialty products to **meet unique specifications**

If you're looking for...

We recommend...

CO₂ removal

UCARSOL™ AP series offers a range of products for CO₂ removal that meet your specific gas treating needs, from pipeline to cryogenic specifications, or lower.

H₂S removal

Including acid gas enrichment and tail gas treating

UCARSOL™ HS series offers economical, proven options where selective separation of CO₂ and H₂S is required.

Mercaptan removal

UCARSOL™ Hybrid series is an innovative option for applications where mercaptan removal is required along with H₂S and/or CO₂ removal.

Bulk removal of acid gas

SELEXOL™ products are cost-effective options for those seeking bulk removal of CO₂, H₂S, and trace sulfur.

Liquid hydrocarbon treatment

Certain **UCARSOL™ products** are designed to minimize hydrocarbon co-absorption, making them ideal for liquid/liquid treating applications.

We're here to help you get more out of your operations.

- 65+ years of gas treating experience
- More than 1,400 references worldwide
- Global distribution network
- Global technical service team operating locally
- Range of in-depth analytical capabilities
- Broad portfolio to address unique needs
- Largest manufacturer of ethanolamines, isopropanolamines and alkanolamines in the world today

Specialty services to **optimize performance**

We offer an array of services in addition to the extensive analytical testing described. These complimentary services include:

- Advanced simulation tools to minimize CAPEX at new facilities
- Plant surveys to optimize performance at existing facilities
- Routine analysis, process monitoring, and troubleshooting
- Simple-to-use online platform to access analytical data
- Assistance in establishing testing capabilities at your site
- Access to world class pilot plant
- Operations training
- Emissions management

Contact us for a system evaluation using our proprietary in-house simulation tools. Alternatively, you can model our most commonly used solvents in commercial software packages – ProMax®, a registered trademark of Bryan Research & Engineering, LLC and ProTreat®, a registered trademark of Optimized Gas Treating, Inc.

A product portfolio **beyond solvents**

Gas treating chelates for redox technology

When amines are used to remove hydrogen sulfide from natural gas, chelates may be required to convert the resulting concentrated H₂S stream into elemental sulfur. We offer IC chelates and process conditioning agents to help abate the H₂S by direct conversion. Chelates can also be used for the direct removal of low levels of H₂S from natural gas streams for conversion to elemental sulfur.

UCARKLEAN™ System for efficient cleaning

We developed our UCARKLEAN™ products as a cost-effective option to remove foulants from your amine unit. Our system removes scale, grease and the hydrocarbon-agglomerated iron sulfide foulant common to amine systems while offering advantages to other cleaning methods today.

The UCARKLEAN™ system offers important advantages over other cleaning methods:

- Simple to use– just mix and dilute with water in your system
- Improved cleaning properties for scale, sludge and grease
- Non-flammable and non-caustic
- Contains no heavy metals
- No neutralization or equipment disassembly required
- Smooth, uneventful start-up after cleaning

US		International		dow.com
Toll Free	800 441 4DOW	Europe / Middle East	+ 800 36 94 63 67	
	989 832 1542	Italy	+ 800 783 825	
		Asia / Pacific	+ 800 77 76 77 76	
			+ 60 37 958 3392	
		South Africa	+ 800 99 5078	

Images: gettyimages_617603080, AdobeStock_216330938, dow_55936893851

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

© 2023 The Dow Chemical Company. All rights reserved.

2000024765-6403

Form No. 812-00064-01-0923 S2D