



Oil & Gas

TECHNICAL INFORMATION

UCARSOL™ AP 810 SOLVENT

FOR CO₂ REMOVAL

INTRODUCTION

UCARSOL™ AP 810 Solvent is one in a series of advanced-performance gas treating solvents from The Dow Chemical Company. Specifically designed for carbon dioxide (CO₂) removal in natural and synthesis gas processing, UCARSOL AP 810 Solvent is effective in both sweet and sour gas streams.

Low heats of reaction, combined with the ability to remove both CO₂ and hydrogen sulfide (H₂S), allow the gas processor to conform to current environmental regulations concerning sulfur emissions, while meeting product gas Btu specifications. UCARSOL AP 810 Solvent is particularly useful for processing feed gas with high amounts of CO₂. It performs well in cryogenic applications with low CO₂ product gas specifications. It may also be used as a bulk CO₂ removal solvent in applications where specifications of 2-3% must be achieved.

SPECIAL FEATURES

UCARSOL™ AP 810 Solvent offers these important advantages versus generic gas treating solvents:

- Significant energy savings through reduced reboiler duty, decreased pumping requirements because of lower solvent circulation, and elimination of the need for solvent reclaiming
- Reduced solvent losses because of low foaming tendency and lower solvent vapor pressure
- Supported by Dow Oil & Gas, the global leader in providing gas treating processors with specialized technology and services
- Increased acid gas processing capacity with existing facilities
- Local technical support is available to assure ongoing trouble-free operation

CORROSION EFFECTS

The results of actual field experience in numerous operating units indicate that solutions of UCARSOL™ AP 810 Solvent, maintained properly and used as specified, exhibit very low corrosion rates.

PHYSICAL PROPERTIES

UCARSOL™ AP 810 Solvent can be used as an aqueous solution in various concentrations; however, a 40-50% aqueous solution has been found to offer optimal performance. Physical property data for pure and 50% aqueous solutions of UCARSOL AP 810 Solvent have been developed and are presented on the following pages.

Additional information on UCARSOL AP 810 Solvent, its properties and its advantages, is available on request. To explore more specifically what UCARSOL AP 810 Solvent can do for your existing or proposed gas treating unit, contact Dow at the numbers listed at the end of this publication.

TABLE 1 • PHYSICAL PROPERTIES OF UCARSOL™ AP 810 SOLVENT

	Pure	50 Wt% Aqueous
Average Weight per Gallon at 20°C, lb	8.71	
Average Weight per Liter at 20°C, kg	1.04	
D lb per Gallon/3t at 20°C	0.00634	
D kg per Liter/3t at 20°C	0.00076	
Coefficient of Expansion at 20°C at 55°C	0.00072 0.00078	
Boiling Point, °C (°F) at 760 mm Hg at 50 mm Hg at 10 mm Hg	149.1 (300.4) 75.2 (167.4) 45.3 (113.5)	103.4 (218.1) 41.5 (106.7) 15.4 (59.7)
Pour Point, °C (°F)	-51.1 (-60)	-15 (5)
pH	10.8	11.5
Specific Gravity, t/20°C	1.0452	1.0469
Solubility in Water at 20°C, weight percent of Water in at 20°C, weight percent	100 100	Complete Complete
Flash Point, °C (°F) Pensky-Martens Closed Cup, ASTM D93 Cleveland Open Cup, ASTM D92	None 132 (270)	

FIGURE 1 • DENSITY OF UCARSOL™ AP 810 SOLVENT




FIGURE 2 • VISCOSITY OF UCARSOL™ AP 810 SOLVENT




FIGURE 3 • HEAT CAPACITY OF UCARSOL™ AP 810 SOLVENT




FIGURE 4 • THERMAL CONDUCTIVITY OF UCARSOL™ AP 810 SOLVENT





FIGURE 5 • SURFACE TENSION OF UCARSOL™ AP 810 SOLVENT

GAS TREATING SERVICES

Dow is a worldwide leader in providing gas treating processors with specialized technology and services. To aid in both plant design and operation, UCARSOL™ solvents are supported by advanced computer capabilities, state-of-the-art laboratory, field test equipment, analytical procedures and an optimization program. The services Dow provides encompass preliminary assessments, start-up services, continual monitoring and follow-up services. Included in this total support program is the training for people in the field, regular sample testing and performance evaluation. To help ensure complete customer protection and satisfaction, Dow is there every step of the way – before, during and after installation.

SIMULATION CAPABILITIES

With information drawn from actual operating conditions of over 1,000 plants, Dow has an extensive formulated solvent database used to optimize the simulation programs used in design. This program provides a powerful tool for process analysis and design, including tray-by-tray calculations. Basic hydraulic evaluations can be made of existing trayed or packed towers to help ensure that conversion to UCARSOL™ solvents will be trouble-free.

Field representatives have the latest equipment and programs that make it possible to predict the performance of UCARSOL solvents under actual plant conditions. In addition, their use as an in-field preliminary design tool is extremely valuable after conversion to make any adjustments necessary to optimize the process.

LABORATORY AND FIELD TESTING

The Dow Oil & Gas Characterization Lab performs regular service analyses of customer solvents to ensure good performance of the amine unit, as well as specialized analyses to assist in trouble-free operation. Routine analysis performed includes ion chromatography, Inductively Coupled Plasma and solution alkalinity. Analysis is normally completed and reported to the customer within a few days upon receiving the sample. Dow's customer report includes a technical service review of the analytical results and their impact on the customer's operation.

SAMPLE KITS

Dow offers a unique sample kit. Completely self-contained, the kit provides everything necessary—from containers to labels—to obtain lean and rich amine samples, seal them, and safely ship them for routine analysis.

OTHER SERVICES

Dow's engineering expertise is also available to provide information on process and equipment requirements. Dow also trains customer personnel prior to and during conversion and follows up with them to ensure optimal performance.

STORAGE AND HANDLING

UCARSOL™ AP 810 Solvent is usually stored and handled in carbon steel equipment. It is also compatible with stainless steel. **Zinc or galvanized steel and copper and its alloys should not be used. Materials of construction guidelines for specific plant areas are available upon request.**

This product becomes viscous at outside winter temperatures and has a pour point of -51.1°C (-60°F). Therefore, storage inside a warm building or in a heated, insulated tank may be desirable. A centrifugal pump is suitable for transfer service, assuming the temperature of the product is sufficiently above its pour point. A rotary or gear pump is suggested for lower temperature transfers.

Piping should be of adequate size to handle the maximum viscosity expected to be encountered. Valves, piping, etc. are usually of steel construction. Type 304 stainless steel, spiral-wound GRAFOIL gaskets for flanges and GRAFOIL packing for valves are recommended.

Aqueous solutions of UCARSOL AP 810 Solvent can be handled in steel equipment. They should **not** be handled or stored in contact with aluminum, zinc or galvanized iron, or with copper and its alloys.

PRODUCT STEWARDSHIP

When considering the use of any Dow products in a particular application, you should review the latest Material Safety Data Sheets from Dow and ensure that they are intended for safe use. For Material Safety Data Sheets and other product safety information, contact Dow. Before handling any other products mentioned in the text, you should obtain available product safety information and take necessary steps to ensure safety of use.

No chemical should be used as or in a food, drug, medical device or cosmetic, or in a product or process in which it may contact a food, drug, medical device or cosmetic until the user has determined the suitability and legality of the use. Since government regulations and use conditions are subject to change, it is the user's responsibility to determine that this information is appropriate and suitable under current, applicable laws and regulations.

Dow requests that the customer read, understand and comply with the information contained in this publication and the current Material Safety Data Sheet(s). The customer should furnish the information in this publication to its employees, contractors and customers, or any other users of the product(s), and request that they do the same.

TO LEARN MORE...

U.S., Canada, Mexico: Phone: 1-800-447-4369 Fax: 989-832-1465

Latin America: Phone: +55 11-5188-9222 Fax: +55-11-5188-9749

Europe, Middle East: Phone Toll Free: +800-3-694-6367*

Phone: +32 3-450-2240 Fax: +32 3-450-2815

Asia Pacific: Phone Toll Free: +800 7776-7776*

Phone: +60 3-7958-3392 Fax: +60 3 7958 5598

Middle East (Dubai): Phone: Tel: +971 4 453 7000 Fax: +971 4 453 7117

North Africa (Cairo): Phone: +202 2 480 1465 Fax: +202 2 480 1478

**Toll-free service not available in all countries.*



Oil & Gas

For more information, visit www.dowoilandgas.com.

Note: This guide is designed as a general product overview. Please contact your local Dow Oil & Gas representative for up-to-date, detailed technical information including registrations and use limitations and to discuss individual applications or requirements.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.