



Technical Data Sheet

WALOCEL™ MKW 15000 PP 30 Cellulose Ether

Hydroxyethyl Methyl Cellulose

Description

WALOCEL™ MKW 15000 PP 30 Cellulose Ether modified hydroxyethyl methyl cellulose (HEMC) is designed to enhance the quality and processing characteristics of cement spray plaster applications such as one- or two-coat cement-based plaster, cement-based lightweight plaster and the cementitious parts of an exterior insulation finishing system (EIFS). Compatible with all conventional mineral binders used in cement spray plaster formulations, WALOCEL™ MKW 15000 PP 30 Cellulose Ether provides sag resistance, high standing strength, effective stabilization of air voids and good impact resistance. It also enhances workability and water retention.

Sustainability Attribute:



Applications

- Decorative renders
- One- or two-coat cement-based plaster
- Cement-based lightweight plaster
- Cementitious parts of an exterior insulation finishing system (EIFS)

Benefits

- Sag resistance
- Quick dissolution
- Excellent adhesion and shear strength
- Good air void stabilization
- High standing strength
- Low stickiness
- High yield

Physical Properties

Property	Unit	Result
Appearance		Powder
Solubility		Water soluble
Viscosity ¹	mPa·s	17500
pH (2% solution)		Neutral
Moisture content, max.	%	7

1. 2% solution in water, Haake Rotovisko RV 100, shear rate 2.55s⁻¹, 20°C
These properties are typical but should not be considered specifications. For detailed specification rates please consult the product Certificate of Analysis..

Health and Safety Considerations

Safety Data Sheets (SDS) is available from The Dow Chemical Company. SDS is provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. SDS is updated regularly, therefore, please request and review the most current SDS before handling or using any product.

WALOCEL™ products have had extensive evaluation in both acute and long-term studies in a number of species, including humans. Their many years of use attest to their safety in a wide variety of applications. While the dust may cause mechanical irritation to the skin and eyes under extreme conditions, the products are considered to present no significant health hazard under normal handling conditions.

Handling and Storage

Cellulose ether products are organic polymers that will burn when exposed to heat and a sufficient oxygen supply. Fires can be extinguished by conventional means, avoiding any raising of dust by strong water jets. Dow recommends the use of water spray, carbon dioxide or powder extinguishers.

During use or storage, safe handling is required to prevent dust with air from reaching explosive levels, as is true with other organic materials of similar particle size. When handling large quantities, local applicable regulations concerning the prevention of dust explosions should be followed. With cellulose ethers, the critical level may be reached at about 28 grams dust/m³. Additionally, WALOCEL™ products, like other organic chemicals, should not be stored next to peroxides or other oxidizing agents.

Solutions of WALOCEL™ products are slippery. To prevent accidents, floor spills of dry powder should be swept up dry. If the spill is a viscous solution, it should be removed by further diluting with water before disposal.

WALOCEL™ cellulose ether products present no significant ecological problems. Typically, they can be disposed of by industrial incineration or in an approved landfill, providing regulations are observed. Customers are advised to review their local, state, provincial, or national regulations governing the disposal of waste materials to confirm the appropriate means of disposal in their area.

Product Stewardship

Dow has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products – from the initial concept and research to manufacture, use, sale, disposal and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

