



Technical Data Sheet

WALOCEL™ M-8804 Cellulose Ether

Hydroxyethyl Methyl Cellulose

Introduction

WALOCEL™ M-8804 Cellulose Ether hydroxyethyl methyl cellulose is designed for use in lightweight tape joint compounds. It imparts well-balanced properties, including excellent open time, tape-bond adhesion and crack resistance. WALOCEL™ M-8804 Cellulose Ether also is designed to provide a good balance of rheological properties, offering outstanding workability for both hand tool and machine tool application. The selected particle size distribution and surface treatment for delayed hydration offer quick, lump-free dissolution. It is compatible with all conventional mineral fillers and organic binders.

Sustainability Attribute:



Typical Physical Properties

These properties are typical but should not be considered specifications.

Property	Unit	Result
Form		Powder
Bulk density	g/L	350–500
Viscosity ¹	mPa•s	36,000–44,000
Moisture content (as packaged)	%, max.	7.0

1. 2% solution in water, Haake Rotovisko RV 100, shear rate 2.55s⁻¹, 20°C

Health and Safety Considerations

WALOCEL™ products have had extensive evaluation in both acute and long-term studies in a number of species, including humans. Their many years of use attest to their safety in a wide variety of applications. While the dust may cause mechanical irritation to the skin and eyes under extreme conditions, the products are considered to present no significant health hazard under normal handling conditions.

Flammability

Cellulose ether products are organic polymers that will burn when exposed to heat and a sufficient oxygen supply. Fires can be extinguished by conventional means, avoiding any raising of dust by strong water jets. Dow recommends the use of water spray, carbon dioxide or powder extinguishers.

Handling

During use or storage, safe handling is required to prevent dust with air from reaching explosive levels as is true with other organic materials of similar particle size. When handling large quantities, local applicable regulations concerning the prevention of dust explosions or those outlined in the National Fire Protection Association (NFPA) Standard: "Prevention of Dust Explosions in Industrial Plants" should be followed. With cellulose ethers, the critical level may be reached at about 28 grams dust/m³. Additionally, WALOCEL™ products, like other organic chemicals, should not be stored next to peroxides or other oxidizing agents.

**Spills/
Housekeeping**

Solutions of WALOCEL™ products are slippery. To prevent accidents, floor spills of dry powder should be swept up dry. If the spill is a viscous solution, it should be removed by further diluting with water before disposal.

Disposal

WALOCEL™ cellulose ether products present no significant ecological problems. Typically, they can be disposed of by industrial incineration or in an approved landfill, providing regulations are observed. Customers are advised to review their local, state, provincial or national regulations governing the disposal of waste materials to confirm the appropriate means of disposal in their area.

**Product
Stewardship**

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

