

**RHOPLEX™ EI-3600**

Acrylic Polymer Emulsion with Fast-Setting Technology

Introduction

RHOPLEX™ EI-3600 emulsion is an all-acrylic waterborne polymer providing fast-set characteristics for various construction and coatings applications. It combines the benefits of acrylic chemistry with the ability to formulate quick-set coatings and related systems.

Typical Applications

- Coated aggregate
- Construction coatings

Advantages

- Excellent durability
- UV resistance
- Fast-setting technology

Typical Physical Properties

These properties are typical but should not be considered specifications.

Appearance	Milky white emulsion
Solids content, %	49.5-50.5
pH	10.0-10.6
Brookfield viscosity, cPs	<250
Glass transition temperature (T _g), °C	25.0
Density, lbs/gal	9.43

**Product
Stewardship**

Dow has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products – from the initial concept and research to manufacture, use, sale, disposal and recycle of each product.

**Customer
Notice**

Dow strongly encourages its customers to review both their manufacturing processes and quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Disclaimer

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean The Dow Chemical Company and its consolidated subsidiaries unless otherwise expressly noted.
NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

CONTACT INFORMATION:
The Dow Chemical Company
100 Independence Mall West
Philadelphia, PA 19106-2399
United States of America
215-592-3000

www.dowconstructionchemicals.com

