

# Technical Data Sheet for Europe, Middle East, Africa and India

### PRIMAL™ 928 ER Acrylic Dispersion

# Product Description

PRIMAL™ 928 ER Acrylic Dispersion is manufactured without added solvent (no solvent intentionally added) for clear and pigmented sealants.

#### **Application**

PRIMAL™ 928 ER is a high performing Acrylic Dispersion that offers sealant formulators to produce both clear and pigmented sealants. Sealants formulated with PRIMAL 928 ER Acrylic Dispersion dry fast, offer remarkable clarity and enhanced resistance to dirt pick-up and blushing.

#### Typical Properties<sup>1)</sup>

Appearance	Milky white liquid	
Tg	-3 °C	
Solids content	62 63%	
рН	4 5	
Density	1.06 g/cm <sup>3</sup>	
Viscosity (Brookfield LV, spindle 2 @ 60 rpm, 25°C)	max. 400 mPa⋅s	
1) Diagram and that the confuse above and topical colors for communications. These are not		

<sup>1)</sup> Please note that the values shown are typical values for your guidance. They are not to be taken as specifications and are subject to certain variability. Please consult the sales specifications for details.

## Health and Safety Considerations

Safety Data Sheets (SDS) are available from The Dow Chemical Company. SDS are provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. SDS are updated regularly, therefore, please request and review the most current SDS before handling or using any product. For further questions consult your Dow contact person.

### Storage and Handling

PRIMAL™ 928 ER Acrylic Dispersion should be stored at temperatures between 5°C and 40°C in tightly sealed containers. Avoid freezing of the material! Upon purchase, applicable legislation on storage must be maintained/followed. PRIMAL 928 ER Acrylic Emulsion Polymer is protected against microbial attack during transportation and storage in not opened original packaging. To avoid problems with microbial attack during processing and in opened packaging, attention should be paid on hygiene. In some cases it could make sense to add biocides under your sole decision to avoid problems with microorganisms. We recommend using the product under safety precautions as described in the SDS. Avoid contact with eyes and skin. Large quantities should be handled in a correctly ventilated area. Material can create slippery conditions. As the product contains water corrosion-resistance equipment should be used for processing. Low shear pumps like diaphragm pumps should be used.

### Product Stewardship

Dow has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product

#### **Customer Notice**

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow

Additional	For more information you may call the following numbers:		
Information	International Toll-Free	<b>00800-3-694-6367</b> International Toll-Free from: Austria, Belgium, Denmark, Finland (prefix 990), France, Germany, Hungary, Ireland, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.	
	EMEAI Toll Call	0031-11567-2626	
	Italy Toll-Free National	00800-783-825	
	South Africa Toll-Free National	00800-99-5078	

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.