

TAMOL™ 1124 Dispersant

Description

TAMOL™ 1124 Dispersant is a high performance hydrophilic copolymer which offers outstanding performance in a wide range of latex paint formulations from high gloss enamels to low sheen flats. Designed for excellent stability and compatibility with modern latex paint additives, TAMOL 1124 Dispersant is an excellent choice for the modern paint formulator.

TAMOL 1124 Dispersant is supplied at high solids (50%) in the ammonia form and was designed to maximize gloss potential where needed, while offering good viscosity, flow and wet adhesion in interior and exterior flat to gloss formulations. It has excellent compatibility with colorants for good color acceptance and is low foaming for ease of use.

TAMOL 1124 Dispersant is a universal dispersant for compatibility with associative rheology modifiers as it is compatible with both anionic HASE and nonionic HEUR rheology modifiers.

Dispersing Efficiency

TAMOL™ 1124 Dispersant should be tested at 0.5% to 1.0% active ingredient based on total pigment weight. It is important to determine the proper level for the finished paint formulation. If a low level is used, the dispersion may be incomplete providing an inadequate grind that will not maximize gloss, hiding or stability. High levels of dispersant may lead to increased water sensitivity.

For more information about formulating with TAMOL 1124 Dispersant, contact your local Dow Technical Representative.

Features	Benefits
Low cost/High performance	Lower formulated cost
Broad formulating range	Wide versatility. Can be used in flats through high gloss formulations
Universal rheology modifiers compatibility	Compatible with both anionic HASE and nonionic HEUR type rheology modifiers
Excellent color compatibility	Excellent color acceptance with high reproducibility
Excellent viscosity stability	Excellent heat-age and shelf stability
High gloss potential	High gloss development
Low foam	Easy to process and handle

Typical and Physical Properties

(These properties are typical but do not constitute specifications).

Property	Typical Values
Appearance	Clear to pale yellow liquid
Chemical Type	Hydrophilic copolymer polyelectrolyte
рН	7.0
Solids, %	50
Brookfield viscosity, cP, as shipped	500 max.
Specific gravity	1.18
Density, lb/gal	10

Handling Precautions

Before using this product, consult the Material Safety Data Sheet (MSDS)/Safety Data Sheet (SDS) for details on product hazards, recommended handling precautions and product storage.

Storage

Store products in tightly closed original containers at temperatures recommended on the product label.

Disposal Considerations

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Coating Materials Technical Representative for more information.

Chemical Registration

Many countries require the registration of chemicals, either imported or produced locally, prior to their commercial use. Violation of these regulations may lead to substantial penalties imposed upon the user, the importer or manufacturer, and/or cessation of supply. It is in your interests to ensure that all chemicals used by you are registered. Dow does not supply unregistered products unless permitted under limited sampling procedures as a precursor to registration.

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Contact:
North America: 1-800-447-4369
Latin America: (+55)-11-5188-9000
Europe: (+800)-3-694-6367
Asia-Pacific: (+800)-7776-7776
http://www.dowcoatingmaterials.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

