

Technical Data Sheet

XIAMETER™ OFX-8040 Fluid

Diamino functional silicone softener

Features & Benefits

Soft, smooth handle

Applications

 Suitable for formulation to a micro emulsion, and, in this form, can be applied to all types of woven or knitted fabric imparting a soft handle.

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Viscosity Measured on Brookfield Cone & Plate at 25°C (77°F)	cPs	800–5000
Nitrogen (by titration with perchloric acid)	%	0.32-0.42
Solis (2 g/1 h/150°C or 302°F)	%	95 minimum

1 1 ~	Τ_	1100
How	10	use

Emulsions of XIAMETER™ OFX-8040 Fluid may be applied by the pad application method for wovens, knits, cotton and polyester-cotton blended fabrics. For optimum, cost effective performance, 0.5 to 0.75% silicone solids "on-weight fabric" should be applied.

XIAMETER OFX-8040 Fluid is suitable for formulation to a micro emulsion.

Handling Precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life And Storage

When stored at or below 30°C in the original unopened containers, this product has a usable life of 18 months from the date of production.

Limitations

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health And Environmental Information To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

http://www.xiameter.com

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

