



XIAMETER™ RBL-2004-75 Liquid Silicone Rubber

75 Shore A durometer, two-part, 1 to 1 mix, translucent, injection molding-grade liquid silicone rubber

Features & Benefits

- Good clarity
- Easily pigmentable
- High hardness
- Formulated to meet FDA 21 CFR 177.2600 and BfR, XV
- UL recognized
- Part design flexibility
- Short cycle time
- Good mechanical properties non post-cure
- Ideal for intricate designs

Applications

This product is designed to provide excellent processing on molding equipment. The balance between short cycle times and superior mechanical properties and transparency makes it suitable for applications such as:

- Diaphragms
- Membranes
- Exhaust hangers
- O-rings
- Grommets
- Gaskets
- Seals
- Drip irrigation (membranes)

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

ASTM ¹	Property	Unit	Value NPC ²
	Extrusion Rate Part A ³	g/min	25
	Extrusion Rate Part B	g/min	30
D792	Specific Gravity		1.15
D2240	Hardness	Shore A	71

1. ASTM: American Society for Testing and Materials.
2. NPC: Non post-cure with initial cure conditions of 5 min at 150°C (302°F).
3. Tested according to Dow Corporate Test Methods.

Typical Properties (Cont.)

ASTM	Property	Unit	Value NPC
D412 DIE C	Tensile Strength	MPa	8.5
		psi	1230
D412 DIE C	Elongation	%	390
D624 DIE B	Tear Strength	kN/m	16
		ppi	90
D149	Dielectric Strength	kV/mm	25.1
UL ⁴ 94 HB	Flammability, Horizontal Burn	HB at 0.38 mm	Rated

4. Underwriters Laboratories

Description

XIAMETER™ RBL-2004-75 Liquid Silicone Rubber is designed to give excellent process performances.

This product answers the needs of special applications where high clarity, high mechanical properties and short cycle time are required.

Thanks to its rheology, this product offers short curing times; however, this characteristic does not affect the pot life of materials when components A and B are mixed together.

How to Use

The A and B components are supplied strained and de-aired to be used as lot matched kits. Mix parts A and B in a 1:1 ratio. Meter mix equipment that pumps, meters and mixes the two components without the incorporation of air is strongly recommended for production. If air bubbles are entrapped during mixing, the mixture must be thoroughly de-gassed under vacuum.

Pot Life

When parts A and B are mixed, the mixture will remain usable for 72 hours at 25°C (77°F).

Cleaning

The uncured silicone can readily be removed by most hydrocarbon solvents. Polar solvents, such as ketones and alcohols, are not suitable.

Curing

XIAMETER™ RBL-2004-75 Liquid Silicone Rubber cures rapidly at elevated temperatures. A 2 mm cross-section requires less than 6 seconds at 200°C (393°F). The cure time depends on the thickness and the cure temperature used. Cure can be inhibited by contact with certain materials, such as amines, sulfur and organotin complexes.

Pigmentation

This is normally carried out during mixing and dispensing of the two components. XIAMETER™ Color Master Batches are recommended with normal additions of 0.5 to 4% based on total volume. These are available from Dow.

Food Contact

XIAMETER™ RBL-2004-75 Liquid Silicone Rubber contains FDA and BfR permitted ingredients, making it suitable for food contact applications.

XIAMETER™ RBL-2004-75 Liquid Silicone Rubber complies with FDA food additive regulation 177.2600 and BfR, XV, which cover rubber articles intended for repeated food contact, provided the rubber is processed using the conditions recommended by these regulations. If your processing conditions vary from these conditions, this product MAY NOT comply with these regulations. Manufacturers should do their own testing to evaluate the level of total extractives for this product as formulated by them and processed under their specific conditions.

For further details on the suitability of this product for food contact applications, please refer to the Food Regulatory Profile.

Handling Precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life and Storage

Product should be stored at or below 32°C (90°F) in original, unopened containers.

Limitations

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health and Environmental Information

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, dow.com or consult your local Dow representative.

Disposal Considerations

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Technical Representative for more information.

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
XIAMETER™ RBL-2004-75 Liquid Silicone Rubber
© 2017–2024 The Dow Chemical Company. All rights reserved.