



Dow performance silicones

Silicone solves high altitude technical challenges at the world's tallest tower

CASE STUDY: BURJ KHALIFA



The project

- With a budget for this project exceeding \$1.5 billion, the final height of the spectacular Burj Khalifa skyscraper soars to 828 m above ground level, holding the record for being the world's tallest building and also for the highest installation of an aluminium and glass facade.
- This iconic project has overcome the greatest of challenges and technical difficulties, not least of which are the wind forces dominating the structural design of the tower, the logistics of moving men and materials at extreme heights and construction of the building envelope.
- A total of 103,000 square metres of glass was used in the cladding panels which are incorporated into a total facade area of 132,190 square metres.
- These advanced cladding panels maximise resistance against heat transmission from the sun and save energy through the use of sophisticated engineering techniques which include high performance reflective glazing.
- Managing the internal pressure foreseen within the insulating glass units due to the high altitude culminated in the specification of DOWSIL™ 3362 Insulating Glass Sealant.

City and country

Dubai, United Arab Emirates

Products*

- DOWSIL™ 993 Structural Glazing Sealant
- DOWSIL™ 3362 Insulating Glass Sealant
- DOWSIL™ 798 Cold and Clean Room Silicone

Key participants

- **Architects**
Adrian Smith, Skidmore, Owings & Merrill
- **Structural glazing fabricators**
Far East Aluminium, Hong Kong
Arabian Aluminium, UAE
- **Insulating glass fabricators**
White Aluminium, UAE
- **Main contractor**
Samsung Engineering & Construction
- **Developer**
Emaar Properties

*Prior to February 2018, products listed were branded as Dow Corning.



- DOWSIL™ 993 Structural Glazing Sealant was specified to bring additional security to the insulating glass units which were mechanically fixed to the superstructure.
- DOWSIL™ 798 Cold and Clean Room Silicone was specified for sealing the exclusive bathrooms within the prestigious apartments.

The Burj Khalifa is part of an extraordinary 500 acre development called Downtown Dubai. The tower's design is derived from patterning systems embodied in Islamic architecture, and also takes inspiration from the harmonious structure of the Hymenocallis plant, which is native to the region. This iconic project breaks many records whilst overcoming the greatest of challenges and technical difficulties, not least of which are the wind forces dominating the structural design of the tower, the logistics of moving men and materials at extreme heights and construction of the building envelope.

The challenge

As with any construction in the Middle East, Dow's technical experts were confronted with testing and specifying products that are able to withstand the rigours of high temperature, ultra-violet light, seismic activity and inclement weather conditions including sandstorms and high winds. In addition, large areas of the curtain wall, which in total is equivalent in size to 17 soccer fields, are positioned at extreme height, which in turn, brings a new set of technical challenges.

The solution

The unitized panels were interlocking on site and up to two storeys tall. Being positioned at such high elevations, the risk of pressure build up within the insulating glass units was alleviated through the specification of DOWSIL™ 3362 Insulating Glass Sealant, as a secondary perimeter seal. Silicone application was carried out by White Aluminium Enterprise who is a member of DOWSIL™ Quality Bond – a recent initiative which provides technical training and support, designed to achieve excellence in quality control, quality assurance and standards of workmanship.

Whilst the shape of the tower along with its height has been varied to minimize wind forces on the building, DOWSIL™ 993 Structural Glazing Sealant plays an important role in providing a strong adhesive bond, UV resistance and fast cure, in the joints between the insulating glass units and the curtain wall frame.

A global leader in silicon-based technology with local and international presence, Dow was readily available to consult



Dow High Performance Building website:

dow.com/construction


 **Visit us on Twitter**
@DowHPBuilding

Image: dow_42924746674

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

© 2021 The Dow Chemical Company. All rights reserved.

2000000943

with customers and supply technical expertise and products to project partners across Europe, Middle East, Korea and China.

DOWSIL™ 3362 Insulating Glass Sealant

A neutral curing silicone sealant specifically formulated for use as a secondary seal in the manufacture of high performance insulating glass units, with outstanding adhesion to a wide range of substrates including coated, enamelled and reflective glass.

DOWSIL™ 3362 Insulating Glass Sealant has excellent temperature stability, is resistant to ozone and ultra-violet radiation and is certified by European Technical Approval ETA 03/0003 and complies with EN 1279 requirements.

DOWSIL™ 993 Structural Glazing Sealant

Certified by European Technical Approval ETA 01/0005, DOWSIL™ 993 Structural Glazing Sealant exhibits excellent weathering properties and high resistance to ultra-violet radiation, heat and humidity once cured. It is ideal for structural bonding of glass and metal, including coated, enamelled and reflective glass.

DOWSIL™ 798 Cold and Clean Room Silicone

A neutral curing, flexible, fungus resistant sealant suitable for use both internally and externally, DOWSIL™ 798 Cold and Clean Room Silicone is highly flexible and has excellent adhesion to a wide range of porous and non-porous surfaces.

About Quality Bond™

Quality Bond™ lifts silicone sealing and bonding to the highest level through the instigation of standards of best practice in quality control, quality assurance and product application by specialist silicone fabricators and applicators. Quality Bond™ allows customers and specifiers to share in Dow's industry-leading expertise and benefit from our proven global performance track record. For more information, please visit: qualitybond.com.

For more information

Learn more about Dow's full range of High Performance Building solutions, including service and support, by visiting us online at dow.com/construction.

Dow has sales offices, manufacturing sites and science and technology laboratories around the globe. Find local contact information at dow.com/contactus.



Contact Dow High Performance Building:

dow.com/customersupport

 **Visit us on LinkedIn**
Dow High Performance Building