



DECLARATION OF PERFORMANCE

No SNF_DOP_001

1. Unique identification code of the product-type:

DOWSIL™ 895 Structural Glazing Sealant

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Effective from 19 February 2014

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Structural sealant glazing systems

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Dow Europe GmbH
Bachtobelstrasse 3
8810 Horgen
Switzerland**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

N/A

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

UBatc

issued:

BCCA 0749

on the basis of:

ETA 01/0005

9. Declared performance

Essential Characteristics	Declared Performance	Harmonized Technical Specification
Specific mass	1.45	ETAG last version
Hardness A	Mean of 33 Shore A	ETAG last version
Design stress in tension	0.14 MPa	ETAG last version
Design stress in dynamic shear	0.14 MPa	ETAG last version
Elastic modulus in tension (E_0)	0.9 MPa	ETAG last version
Elastic modulus in shear tangential to the orgin (G_0)	0.3 MPa	ETAG last version
Working time (25°C, 50%RH)	15 min	ETAG last version
Skin over time (25°C, 50%RH)	15 min	ETAG last version
Tack free time (25°C, 50%RH)	30–50 min	ETAG last version
Time before transport of the bonded frame	Min 21 days	ETAG last version
Tensile strength, H-Bar (ALU-GL), 23°C-50RH + 1 d H ₂ O	> 0.70 MPa	ETAG last version
COH. Failure 100%, H-Bar (ALU-GL), 23°C-50RH	100%	ETAG last version

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sebastien Dath
High Performance Building AETS Manager EMEA
Sebastien.dath@dow.com

Seneffe, 1 October 2019

Disclaimer: The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Chemical Company makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.