



January 15, 2021

Attention: Dow Silicones Corporation Customer

Re: Sealant Certification for: **DOWSIL™ 758 Silicone Weather Barrier Sealant**

DOWSIL™ 758 Silicone Weather Barrier Sealant meets or exceeds the following specifications:

- ASTM C 920, Standard Specification for Elastomeric Joint Sealants, Type S, Grade NS, Class 25, Use NT.
- SWRI Sealant Validation, Pass ✓ Extension +25% Compression -25%

On behalf of Dow, we appreciate your business and your commitment to silicone technology. If you have any further questions, please feel free to contact us.

Sincerely,

Dow Silicones Corporation
Technical Customer Service, Construction
+1 800 248 2481 Option 1
na.info@dow.com
dow.com/contactus

DOW HIGH PERFORMANCE BUILDING SOLUTIONS

Imagine the Possibilities

dow.com/construction

63-6399-01 0121



®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
© 2021 The Dow Chemical Company. All rights reserved.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.