



Technical Data Sheet

DOWSIL™ 11-100 Additive CN

A functional siloxane for low smoke halogen free wire & cable material LOI improvement and inorganic filler surface treatment

Features & Benefits

- Increase LOI value
- Improve inorganic filler de-agglomeration
- Impart hydrophobicity to inorganic filler surface
- Longer shelf life
- High quality consistency
- Low viscosity
- Meet higher customer LOI specific requirement
- Improve process stability and productivity of compounding
- Longer inventory window

Composition

- Alkoxy siloxane

Applications

- Low smoke halogen free wire & cable material
 - Improve LOI (Limiting Oxygen Index) value
 - Improve filler dispersion in polymer matrix
- Inorganic fillers surface treatment
 - Improve de-agglomeration
 - Impart hydrophobicity

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Appearance		Clear liquid, no gel
Specific Gravity		0.97
Viscosity @ 25°C	cSt	5.5
Freeze Point	°C	< -16
Actives Content	wt%	> 90
Flash Point	°C	16

Materials were tested according to Corporate Test Methods (CTM).
Copies of CTMs are available on request.

Description

DOWSIL™ 11-100 Additive CN contains alkoxy and alkyl functional groups on siloxane to improve LOI value for low smoke halogen free wire & cable material and improve dispersion of inorganic fillers, such as ATH/MDH etc into organic polymers such as resin, plastic, and rubber. It also will transform hydrophilic inorganic powders, fillers, or substrates to that of hydrophobic. The alkoxy groups react similarly to that of silane coupling agents, forming a stable bond with the mineral filler or surface. The alkyl functionality acts as both compatilizer with organic polymer matrices, as well as hydrophobe to reduce water absorption. This material is also low viscosity and can be applied easily.

How to Use

DOWSIL™ 11-100 Additive CN can be applied to mineral fillers and inorganic surfaces by pre-treatment or in-situ mixing, i.e. during compounding with a polymer resin or rubber (Such as EVA, PP, PE, PU).

In-Situ Application

This additive could be added to the extruder or mixer directly at a level of approximately 1% (for 1–10 micron size particles) based on the weight of the mineral filler. In some cases, it may be upwards of 2–3%. For each specific application, the optimum loading should be determined by testing several loadings. Because this product contains methanol and will generate methanol during the mixing process at elevated temperature, a vent should be provided and safe handling of this vent stream should be considered.

Pre-Treatment

This product can be applied directly to a mineral filler by atomizing onto a well mixed (preferably in a fluidized state for best mixing) powder. Or it can be applied by dipping, brushing, or spraying onto a surface. The additive can be applied neat or in a dilute solution of aliphatic hydrocarbon solvent, aromatic hydrocarbon, or anhydrous alcohol, generally at a level of 1% (for 1–10 micron size particles) by weight of mineral filler powders. Higher surface area substrates would require a higher percentage of DOWSIL™ 11-100 Additive CN by weight, generally 2–3%. After application, the inorganic powder/ substrate should then be air dried at ambient conditions or dried briefly at 105°C to 120°C (221–248°F) to complete condensation of silanol groups at the surface and to remove methanol and water. Optimum treatment level, application, and drying conditions, such as time and temperature, should be determined for each application prior to use in a commercial process. This product contains residual methanol and will also generate methanol upon reaction, so appropriate handling should be considered.

Handling Precautions

This product contains residual methanol and is flammable. Also when exposed to moisture, DOWSIL™ 11-100 Additive CN hydrolyses, generating methanol. Appropriate measures should be taken to prevent the accumulation of hazardous concentrations of methanol fumes in the working environment.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life and Storage

After opening a container of DOWSIL™ 11-100 Additive CN, a partially filled container should be protected from atmospheric moisture to prevent gelation by purging the container with dry nitrogen or other dry, inert gas. When stored at or below 25°C (77°F) in the original unopened containers, this product has a usable life of at least 18 months from the date of production.

Packaging Information

This product is available in 18 kg pails and 195 kg drums. Samples are available in 500 ml bottles.

Limitations

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health and Environmental Information

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, dow.com or consult your local Dow representative.

How Can We Help You Today?

Tell us about your performance, design, and manufacturing challenges. Let us put our silicon-based materials expertise, application knowledge, and processing experience to work for you.

For more information about our materials and capabilities, visit **dow.com**.

To discuss how we could work together to meet your specific needs, go to **dow.com** for a contact close to your location. Dow has customer service teams, science and technology centers, application support teams, sales offices, and manufacturing sites around the globe.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

