



Technical Data Sheet

Dow PuraGuard™ Propylene Glycol USP/EP

General Description

Dow PuraGuard™ Propylene Glycol USP/EP (Dow PuraGuard™ PG USP/EP), referring to the United States and European Pharmacopoeias, is a high-purity grade of monopropylene glycol for use in pharmaceutical, food, cosmetic, personal care, flavor and fragrance, plus a variety of other applications.

The clear, colorless, practically odorless, slightly viscous, water-soluble and hygroscopic liquid with low vapor pressure is produced and handled in compliance with current Good Manufacturing Practice (cGMP) guidelines.

Dow PuraGuard™ PG USP/EP is tested for compliance with the current USP, EP, and Japanese Pharmacopoeia (JP) specifications plus the Food Chemical Codex (FCC); it also complies with the Brazilian Pharmacopoeia, and other pharmaceutical, cosmetic and food regulations in the global markets where it is sold. It is listed by the Cosmetic, Toiletry and Fragrance Association as an approved ingredient in cosmetics and its use is reviewed by the Cosmetic Ingredient Review (CIR). Dow PuraGuard™ PG USP/EP is Kosher and Halal certified.

Typical

Properties⁽¹⁾

Chemical Name	1,2-Propanediol
Formula	$\text{CH}_3\text{-CH(OH)-CH}_2\text{OH}$; $\text{C}_3\text{H}_8\text{O}_2$
Molecular Weight (g/mol)	76.10
CAS Number	57-55-6
EINECS Number	200-338-0
Assay	> 99.8% by weight
Water	< 0.2% by weight
Boiling Point, 101.3 kPa (1 atm)	187°C (369°F)
Distillation Range, 101.3 kPa (1 atm)	186–189°C (367°F–372°F)
Vapor Pressure, 20°C (68°F)	0.011 kPa (0.08 mm Hg)
25°C (77°F)	0.017 kPa (0.13 mm Hg)
Freezing Point	Super cools
Pour Point	< -57°C (-71°F)
Specific Gravity 20/20°C (68/68°F)	1.038
25/4°C (77/39°F)	1.033
60/4°C (140/39°F)	1.007
Refractive Index n ₂₀ /D, 20°C (68°F)	1.4310–1.4330
Viscosity, 25°C (77°F)	48.6 centipoise (mPa.s)
60°C (140°F)	8.4 centipoise (mPa.s)
Specific Heat, 25°C (77°F)	2.51 J/g°K
Surface Tension, 25°C (77°F)	36 mN/m
Flash Point, Pensky-Martens Closed Cup	104°C (220°F)
Autoignition Temperature	371°C (700°F)
Thermal Conductivity, 25°C (77°F)	0.2061 W/m°K
Electrical Conductivity, 25°C (77°F)	10 micro S/m
Heat of Formation	-422 kJ/mol (-101 Kcal/g-mol)
Heat of Vaporization, 25°C (77°F)	67.0 kJ/mol

1. These data are laboratory results typical of the product, and should not be confused with, or regarded as specifications.

Sales Specification and Certificate of Analysis

The sales specification of Dow PuraGuard™ Propylene Glycol USP/EP contains all original specification items listed in the current USP, EP, JP and FCC, plus a number of Dow-specific test items. Key product parameters are analyzed on every lot, and the complete set of monograph specification items are analyzed on a skip-lot basis once per quarter.

Lot-specific Certificates of Analysis (CoA) are provided for every product shipment, containing test results for all USP, EP, JP and FCC items and clearly differentiating between actual and skip-lot results.

A very high dedication to consistent quality and purity governs the entire product supply process for Dow PuraGuard™ Propylene Glycol USP/EP.

Purity Plus

Purity Plus describes Dow's dedication to pure excellence in propylene glycol:

- Purity means producing and handling Dow PuraGuard™ PG USP/EP according to the industry's most stringent standards.
- Plus refers to the support and confidence our customers have in Dow – with nearly 60 years of PG experience, global customer and technical support, excellent product stewardship, and environment, health and safety practices.

Applications

Dow PuraGuard™ Propylene Glycol USP/EP is a widely used ingredient in pharmaceutical, food, cosmetic, personal care, flavors and animal feed applications; an overview of typical uses of Dow PuraGuard™ PG USP/EP is given below.

It must be emphasized that it is the user's responsibility to consult area and country-specific regulations for details of approved use.

1. Pharmaceuticals - Solvent for active ingredients in oral and topical drug products as an excipient.
2. Cosmetics & Personal Care - Solvent, coupling agent, carrier, emulsion stabilizer, softening agent, viscosity modifier and humectant in many types of cosmetics and personal care products such as skincare, sun care, shampoo, bath/shower products, toothpastes, mouthwashes, shaving products and baby care products.
3. Flavors & Fragrances - Solvent and extraction solvent of flavors and fragrances for applications in food, beverages, perfumes and cosmetics.
4. Food - Various applications as a direct food additive (applicable 21 CFR, E 1520) such as a carrier or carrier solvent for colors, emulsifiers, antioxidants and enzymes (in Europe with maximum 1 g/kg in human foodstuffs), and humectant and stabilizer in fruits, vegetables and bakery goods (except in Europe). PG USP/EP is also applied in indirect contact food applications, such as a low temperature heat-transfer fluid in the brewing, dairy and ice cream industries and for food storage facilities, an equipment cleaner fluid or a solvent for printing inks.
5. Pet foods & Animal Feed - Humectant, emulsifier, preservative, solvent for additives (in Europe with different maximum contents for specific species), energy source and aid for prevention of ketosis (acetonemia) in dairy cattle. Consult regulations for species specific information.

Application-specific information for Dow PuraGuard™ PG USP/EP is available from application overview data sheets.

Formulation Advantages

- Excellent solvent action for a variety of flavoring, fragrance and active drug ingredients
- High humectant values for providing moisture retention in products
- Low volatility
- Absence of odor and color
- Plasticizing and softening agent
- Complete water solubility
- Excellent solubility for other organic materials

Storage and Handling

Dow PuraGuard™ Propylene Glycol USP/EP is stable for at least two years when stored at ambient temperatures in closed containers and away from sunlight and other sources of UV light.

Where product heating is utilized (i.e. for bulk storage and/or transport containers) the product temperature should be controlled to prevent unintentional overheating over extended periods as this may potentially lead to accelerated oxidative degradation of the product. As a general guide Dow recommends heating up to not more than 40° C.

For more details about product handling and safety information, please refer to the Dow Safety Data Sheet (SDS).

Product Stewardship

The Dow Chemical Company and its subsidiaries ("Dow") has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Safety Considerations

Material Safety Data (MSD) sheets are available from The Dow Chemical Company. MSD sheets are provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. MSD sheets are updated regularly, therefore, please request and review the most current MSD sheet before handling or using any product. These are available on Dow.com.

Customer Notice

Dow encourages its customers to review their application of Dow products from the standpoint of human health and environmental quality. To help ensure that Dow products are not used in ways for which they were not intended or tested, Dow personnel will assist customers in dealing with ecological and products safety. Your Dow sales representative can arrange the proper contacts.

Contact information:

For more information about this product please call The Dow Chemical Company.

North America: 1-800-447-4369
Latin America: (+55) 11-5184-8722
Europe: (+31) 11-567-2626
Asia/Pacific: (+60) 3-7965-5392
<http://www.dow.com/>

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED

