



TECHNICAL INFORMATION

ACCENT™ 1100 SCALE INHIBITOR

PRODUCT DESCRIPTION/APPLICATIONS

ACCENT™ 1100 Scale Inhibitor is a low-molecular-weight acrylic polymer used to treat scale issues in common oilfield water conditions. ACCENT 1100 Scale Inhibitor is OSPAR compliant for use in offshore applications.

ACCENT 1100 Scale Inhibitor can be used in oilfield water treatment to prevent mineral scale in both downhole and topside production equipment. Depending on the location of scaling, ACCENT 1100 can be delivered continuously downhole or topside, or via squeeze application.

ACCENT 1100 Scale Inhibitor has a traceable version, ACCENT 1100T Traceable Scale Inhibitor, which offers similar performance with an innovative polymer detection system that can reduce operating costs. Please see the ACCENT Traceable Scale Inhibitor System brochure (Form number 812-00024) or contact your Dow representative for more information.

FEATURES AND BENEFITS OF ACCENT™ 1100 SCALE INHIBITOR

- Efficient mineral scale inhibitor for calcite (CaCO₃), barite (BaSO₄) and calcium sulfate (CaSO₄)
- Offers strong dispersant activity when compared to phosphonate performance
- Contains no phosphorus, allowing use where legislation prohibits phosphorus discharge
- Excellent stability at high temperatures with formulation capability over a wide range of pH conditions
- Good stability with freeze-protecting solvents, such as ethylene glycol and methanol

TABLE 1 • PERFORMANCE ATTRIBUTES OF ACCENT™ 1100 SCALE INHIBITOR

| Inhibition Performance | | | | | Stability Performance | | | | |
|------------------------|--|-------------------|---------------|-----------|-----------------------|----------------|---------------|---------------------|---------------------|
| CaCO ₃ | BaSO ₄ / SrSO ₄ | CaSO ₄ | Silica | Thermal | Divalent Brines | High pH Brines | Low pH Brines | MeOH Rich Solutions | MeOH Lean Solutions |
| Above Average | Above Average | Above Average | Below Average | Excellent | Average | Excellent | Above Average | Below Average | Excellent |

TABLE 2 • TYPICAL PROPERTIES OF ACCENT™ 1100 SCALE INHIBITOR

THESE PROPERTIES DO NOT CONSTITUTE SPECIFICATIONS.

| Property | Typical Value |
|--|---------------------------------|
| Appearance | Clear to slightly hazy solution |
| Average Molecular Weight (Mw) | 2,000 |
| Total Solids (%) | 48 |
| pH (at 25°C) | 3.6 |
| Bulk Density (at 25°C) | 1.25 |
| Brookfield Viscosity (mPa.s/cps at 25°C) | 200 |

STORAGE AND PACKAGING RECOMMENDATIONS

ACCENT™ 1100 Scale Inhibitor is available in 238kg drums, 1,180kg totes and bulk quantities. Freezing or long-term cold storage of ACCENT 1100 Scale Inhibitor may cause some separation of the components. Although product performance is not impaired as long as the whole container is heated and well mixed, preventing ACCENT 1100 Scale Inhibitor from freezing is recommended. Freeze-protected formulations can be developed for these materials. Please contact your local Dow representative for more details.

PRODUCT STEWARDSHIP

When considering the use of any Dow products in a particular application, you should review the latest Material Safety Data Sheets from Dow and ensure that they are intended for safe use. For other products mentioned in the text, you should obtain the current Material Safety Data Sheet and other available product safety information when reviewing and take necessary steps to ensure safety of use before handling.

No chemical should be used as or in a food, drug, medical device, or cosmetic, or in a product or process in which it may contact a food, drug, medical device or cosmetic until the user has determined the suitability and legality of the use. Since government regulations and use conditions are subject to change, it is the user’s responsibility to determine that this information is appropriate and suitable under current, applicable laws and regulations.

Dow requests that the customer read, understand and comply with the information contained in this publication and the current Material Safety Data Sheet(s). The customer should furnish the information in this publication to its employees, contractors and customers, or any other users of the product(s), and request that they do the same.

TO LEARN MORE...

U.S., Canada, Mexico: Phone: 1-800-447-4369 Fax: 989-832-1465

Latin America: Phone: +55 11-5188-9222 Fax: +55-11-5188-9749

Europe: Phone Toll Free: +800-3-694-6367*

Phone: (+32) 3-450-2240 Fax: +32 3-450-2815

Asia Pacific: Phone Toll Free: +800 7776-7776*

Phone: (+60) 3-7958-3392 Fax: +60 3 7958 5598

Middle East and North Africa: Phone: +971 4 332 8866

Fax: +971 4 332 8280

Cairo, Egypt: Phone: +202 2 480 1465 Fax: +202 2 480 1478

**Toll free service not available in all countries.*



Oil & Gas

For more information, visit www.DowOilandGas.com.

Note: This guide is designed as a general product overview. Please contact your local Dow Oil & Gas representative for up-to-date, detailed technical information including registrations and use limitations and to discuss individual applications or requirements.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.