



Technical Data

ROMAX™ 6005

Water Clarifier

Description

ROMAX™ 6005 Water Clarifier is an effective solution that provides a cost-effective method for separating oil from produced water. ROMAX 6005 Water Clarifier is a waterborne polymer that is added to produced water streams at doses of 10-100 ppm.

Features and Benefits

- Excellent oilfield water clarifier
- Ready to dose
- Low-viscosity material
- Excellent temperature stability

Typical Properties

Property	Typical Value
Appearance	White Liquid
Emulsion Type	Anionic
Actives (%)	14
pH (as supplied)	5.0
Specific Gravity, g/cm ³	1.03
Viscosity (as supplied), cP	<10

These properties do not constitute specifications.

Thermal Stability

ROMAX™ 6005 Water Clarifier is designed to be pumpable at temperatures as low as 5°C and is stable for short-term exposures of up to 60°C.

Storage and Packaging Recommendations

ROMAX™ 6005 Water Clarifier is available in 200 kg drums. Please contact your local Dow representative for more details.

Product Stewardship

When considering the use of any Dow products in a particular application, you should review the latest Material Safety Data Sheets from Dow and ensure that they are intended for safe use. For Material Safety Data Sheets and other product safety information, contact Dow. Before handling any other products mentioned in the text, you should obtain available product safety information and take necessary steps to ensure safety of use.

No chemical should be used as or in a food, drug, medical device or cosmetic, or in a product or process in which it may contact a food, drug, medical device or cosmetic until the user has determined the suitability and legality of the use. Since government regulations and use conditions are subject to change, it is the user's responsibility to determine that this information is appropriate and suitable under current, applicable laws and regulations.

Dow requests that the customer read, understand, and comply with the information contained in this publication and the current Material Safety Data Sheet(s). The customer should furnish the information in this publication to its employees, contractors and customers, or any other users of the product(s), and request that they do the same.

The Dow Chemical Company

U.S., Canada, Mexico:

Toll Free 1-800-447-4369

Latin America: (+55) 11-5188-9222

Europe:

Toll Free +800-3-694-6367*
(+32) 3-450-2240

Asia Pacific:

Toll Free +800-7776-7776*
(+60) 3-7958-3392

Middle East (Dubai): +971-4-453-7000

North Africa (Cairo): +202-2-480-1466

*Toll-free service not available in
all countries

www.dowoilandgas.com

Note: This guide is designed as a general product overview. Please contact your local Dow representative for up-to-date, detailed technical information including registrations and use limitations and to discuss individual applications or requirements.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

