



## Technical Data Sheet

### **RHOPLEX™ EI-2000**

100% acrylic polymer

#### **Description**

RHOPLEX™ EI-2000 is a versatile 100% acrylic polymer designed for use as a binder for exterior insulation and finish systems (EIFS) and as a cement modifier. Because it is cement-compatible, it offers excellent performance in EIFS cementitious basecoats and adhesives. Due to its 100% acrylic composition, it imparts good exterior durability

#### **Applications**

- EIFS
- Portland Cement Modifier

#### **Benefits**

- Excellent Dirt Pickup Resistance
- High degree of UV resistance
- Good high-temperature pot life
- Good Flexibility
- Water, yellowing and chalking resistance
- Strength, adhesion and water resistance (Portland Cement).
- Flexibility and durability of the cement components (Portland Cement).

#### **Physical Properties**

Appearance	White, milky liquid
Solids (Wt. %)	46.5 ± 0.5
pH	9.0-9.6
Density (lb/gal)	8.80
Brookfield Viscosity, cps (#2 @ 30 RPM)	10-300
(MFFT), °C	5-9

These properties are typical but should not be considered specifications. For detailed specification rates please consult the product Certificate of Analysis.

#### **Health & Safety Considerations**

Safety Data Sheets (SDS) are available from The Dow Chemical Company. SDS are provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. SDS are updated regularly, therefore, please request and review the most current SDS before handling or using any product. For further questions consult your Dow contact person.

## Handling & Storage

RHOPLEX™ EI - 2000 should be stored at temperatures between 5°C and 40°C in tightly sealed containers. Avoid freezing of the material. Local legislation on storage must be followed.

We recommend using the product under safety precautions as described in the SDS. Avoid contact with eyes and skin. Large quantities should be handled in a correctly ventilated area. Material can create slippery conditions. As the product contains water corrosion-resistance equipment should be used for processing. Low shear pumps like diaphragm pumps should be used.

## Product Stewardship

Dow has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products – from the initial concept and research to manufacture, use, sale, disposal and recycle of each product.

## Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

**For further information contact:**  
North America +800-783-825 (free)  
Europa, India, Africa, Middle East:  
+800-3-694-6367 (free)  
America Latina: +55-11-5188-9000  
Pacifico: +800-7776-7776 (free)

<http://www.dow.com>

Disclaimer: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted.

**NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

