



POLYCO™ 2160 Polyvinyl Acetate Homopolymer
For Paper and Paperboard Coatings

Regional Product Availability

- North America

Description

Polyvinyl acetate homopolymer for Paper and Paperboard coatings

Carboxylated Polyvinyl Acetate Homopolymer with excellent mechanical stability and very low grit levels. Medium particle size with good pigment binding ability and excellent water resistance. Minimizes "water interference mottle" in offset printing and offers good ink receptivity, glueability, and brightness with very low odor. POLYCO™ 2160 Polyvinyl Acetate Homopolymer meets new food compliance requirements (listed below).

Typical Properties

These properties are typical but do not constitute specifications

Property	Typical Values
Ionic Nature	Anionic
Solids %:	50
pH as packed:	7.0
Brookfield viscosity, cP:	30
Glass Transition Temperature (Tg °C)	+37
Density, 25 °C, lbs./US gallon	9.0
Specific Gravity	1.08

UNRESTRICTED – May be shared with anyone

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
POLYCO™ 2160 Polyvinyl Acetate Homopolymer / Dow Coating Materials



FDA STATUS

FDA Regulation	Complies	Limitations	Opinion Date
<p>21CFR176.170 Components of paper and paperboard in contact with aqueous and fatty foods</p>	<p>Yes; with limitations as noted</p>	<p>Provided that the food contact surface of the paper and paperboard complies with the Extractives Limitations in 21CFR176.170 paragraph (C)</p>	<p>9/21/2012</p>
<p>21CFR176.180 Components of paper and paperboard in contact with dry food</p>	<p>Yes, with limitations as noted</p>	<p>Must not exceed 49°C (120°F)</p>	<p>9/21/2012</p>

All components used in the manufacturing of POLYCO™ 2160 Emulsion are listed either in BfR-Recommendation XIV-A (Plastics Dispersions) or in BfR-Recommendation XXXVI (Paper and board for food contact). Some components are subject to a restriction. This proprietary information will be supplied upon your request following terms and conditions in agreement with the Company policies. Please contact our Customer Information Group (CIG@DOW.com) for more details.

UNRESTRICTED – May be shared with anyone
 *™ Trademark of The Dow Chemical Company (“Dow”) or an affiliated company of Dow
 POLYCO™ 2160 Polyvinyl Acetate Homopolymer / Dow Coating Materials

Handling Precautions	Before using this product, consult the Material Safety Data Sheet (MSDS)/Safety Data Sheet (SDS) for details on product hazards, recommended handling precautions and product storage.
Storage	Store products in tightly closed original containers at temperatures recommended on the product label.
Disposal Considerations	Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.
Product Stewardship	<p>It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Coating Materials Technical Representative for more information.</p> <p>Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.</p>
Customer Notice	Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Contact:
North America: 1-800-447-4369
Latin America: (+55)-11-5188-9000
Europe: (+800)-3-694-6367
Asia-Pacific: (+800)-7776-7776
<http://www.dowcoatingmaterials.com>

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



UNRESTRICTED – May be shared with anyone
[®]™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
POLYCO™ 2160 Polyvinyl Acetate Homopolymer / Dow Coating Materials