



RHOPLEX™ WL-91 Emulsion

Waterborne Acrylic Copolymer for Industrial Coatings

Introduction

RHOPLEX™ WL-91 Emulsion is a hard, acrylic-styrene copolymer designed for waterborne clear and pigmented industrial finishes for metal, concrete, plastic and wood substrates. Suitable for both ambient and forced dry industrial primers and lacquers, RHOPLEX™ WL-91 Emulsion facilitates the formulation of coatings with an attractive appearance, excellent chemical and solvent resistance, hardness, adhesion and corrosion resistance.

RHOPLEX™ WL-91 Emulsion is recommended for use in fast-drying metal primers and direct-to-metal (DTM) finishes over untreated and treated metals. With excellent resistance to chemicals and oil and good film toughness, it also performs well in concrete sealers and floor tile sealers

Features & Benefits

- Excellent chemical and solvent resistance
- Lacquer-like fast drying and rapid hardness development
- High gloss and excellent appearance
- Good corrosion resistance over metals
- Excellent adhesion to a variety of substrates
- Good stability when formulated with anti-corrosive pigments
- Self-thickening, sometimes eliminating the need for additional rheology modifiers

Typical Physical Properties

These properties are typical but do not constitute specifications.

Property	Typical Values
Appearance	Milky, White Liquid
Solids Content, %	41.5
pH	7.5
Viscosity, cP (#3 Spindle @ 60 rpm, 25°C)	< 1000 cP
Weight per U.S. Gallon (Wet, lbs/gal)	8.6
Bulking Value (Wet), gal/lbs	0.116
Bulking Value (Dry), gal/lbs	0.110
MFFT (°C)	52

Potential Applications

- General industrial finishes for metal, wood and plastic
- Industrial maintenance finishes for steel and concrete
- Concrete sealers and pigmented coatings
- Floor tile sealers

**Handling
Precautions**

Before using this product, consult the Material Safety Data Sheet (MSDS)/Safety Data Sheet (SDS) for details on product hazards, recommended handling precautions and product storage.

Storage

Store products in tightly closed original containers at temperatures recommended on the product label.

**Disposal
Considerations**

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Coating Materials Technical Representative for more information.

**Chemical
Registration**

Many countries require the registration of chemicals, either imported or produced locally, prior to their commercial use. Violation of these regulations may lead to substantial penalties imposed upon the user, the importer or manufacturer, and/or cessation of supply. It is in your interests to ensure that all chemicals used by you are registered. The Dow Chemical Company does not supply unregistered products unless permitted under limited sampling procedures as a precursor to registration.

**Product
Stewardship**

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Contact:

North America: 1-800-447-4369
Latin America: (+55)-11-5188-9000
Europe: (+800)-3-694-6367
Asia-Pacific: (+800)-7776-7776
www.dow.com

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

