



EXTERIOR INSULATION - TWO LAYERS STAGGERED TO MINIMIZE GAP IN THERMAL BARRIER

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING - LAP FULLY OVER STS

4" MIN. WIDE DOWSIL™ SILICONE TRANSITION STRIP (SDS) SEALED OVER GAP WITH 2" MIN. BOND EACH SIDE. DO NOT SEAL GAP

CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT CAP ALONG EDGE OF SILICONE TRANSITION STRIP

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

2b ALTERNATE 2 - CONTROL JOINT DETAIL (PLAN)
 SCALE: 3"=1'-0"

61-8021-01 C



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NUMBER

02b

DATE

11/1/2019