



- EXTERIOR GRADE GYPSUM BOARD SUBSTRATE
- DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING
- CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT CAP ALONG EDGE OF DOWSIL™ SILICONE TRANSITION STRIP (STS) AND METAL FLASHING, TYP.
- 4" MIN. WIDE DOWSIL™ SILICONE TRANSITION STRIP (STS) SEALED INTO WINDOW MULLION WITH DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT, LAP 2" MIN. ONTO SHEATHING
- EXTERIOR CLADDING ASSEMBLY BY OTHER
- METAL DRIP FLASHING
- CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

01 **DETAIL SECTION: WINDOW HEAD - CURTAIN WALL AT MTL. STUD WALL**
SCALE: 3"=1'-0"

61-8033-01 D



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.	08
DATE	11/1/2019