



EXTERIOR GRADE GYPSUM BOARD SUBSTRATE

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT CAP ALONG EDGE OF DOWSIL™ SILICONE TRANSITION STRIP (STS) AND METAL FLASHING, TYP.

4" MIN. WIDE DOWSIL™ SILICONE TRANSITION STRIP SEALED ONTO WINDOW MULLION WITH DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT, LAP 2" MIN. ONTO SHEATHING

EXTERIOR CLADDING ASSEMBLY BY OTHER

METAL DRIP FLASHING

CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

01

DETAIL SECTION: WINDOW HEAD
PROJECTED CURTAIN WALL AT MTL. STUD WALL

SCALE: 3"=1'-0"

61-8041-01 D



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.
DATE

14

11/1/2019