



EXTERIOR GRADE GYPSUM BOARD SUBSTRATE

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING CONTINUE ALONG SUBSTRATE AND CONCRETE SLAB EDGE

4" MIN. WIDE DOWSIL™ SILICONE TRANSITION STRIP (STS) SEALED OVER GAP WITH 2" MIN. BOND EACH SIDE OF DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING COATED SURFACE. DO NOT SEAL GAP, TYP.

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT BEAD IN JOINT, TYP.

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT CAP ALONG METAL FLASHING

CONTINUOUS METAL FLASHING THROUGH WALL BY OTHER

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT CAP ALONG EDGE OF DOWSIL™ SILICONE TRANSITION STRIP, TYP.

EXTERIOR CLADDING ASSEMBLY BY OTHER

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

01 **DETAIL SECTION:**
MTL. STUD WALL AT FLOOR SLAB
SCALE: 3"=1'-0"

61-8046-01 D



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.
DATE

20

11/1/2019