



CONTINUOUS CAP BEAD OF DOWSIL™ 791 WEATHERPROOFING SEALANT, FULLY COVER WITH DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING CONTINUE ALONG SUBSTRATE AND CONCRETE SLAB EDGE

SEE DETAIL 47b FOR APPLICATION OF DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING AT CONCRETE- EMBEDDED ASSEMBLIES

EXTERIOR CLADDING ASSEMBLY BY OTHER

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT FILLET BEAD IN CORNER TO SUPPORT APPLICATION OF DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING - SEALANT TO HAVE MIN. 1/4" BITE ONTO SUBSTRATES

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

01

**ALT.1 DETAIL SECTION:
COLD SOFFIT**

SCALE: 3"=1'-0"

61-8059-01 D



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.	34A
DATE	11/1/2019