



- CMU
- APPLY DOWSIL™ 778 SILICONE LIQUID FLASHING OR DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING
- CONTINUOUS DOWSIL™ 791 WEATHERPROOFING SEALANT CAP ALONG EDGE OF DOWSIL™ SILICONE TRANSITION STRIP (STS), TYP.
- DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING
- BRICK VENEER
- 4" MIN. WIDE DOWSIL™ SILICONE TRANSITION STRIP (STS) SEALED INTO WINDOW MULLION - LAP 2" MIN. ONTO SHEATHING
- CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT
- DOWSIL™ SILICONE SEALANT W/ BACKER ROD, TYP.

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

107 DETAIL PLAN:
CURTAINWALL AT BRICK W/ CMU WALL
SCALE: 3"=1'-0"

61-8094-01 C



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.	107
DATE	11/1/2019