



CMU

APPLY DOWSIL™ 778 SILICONE LIQUID FLASHING OR DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING

CONTINUOUS DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT CAP ALONG EDGE OF DOWSIL™ SILICONE TRANSITION STRIP (STS), TYP.

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING

BRICK VENEER

4" MIN. WIDE DOWSIL™ SILICONE TRANSITION STRIP(STS) SEALED INTO WINDOW MULLION - LAP 2" MIN. ONTO SHEATHING

CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT

DOWSIL™ SILICONE SEALANT W/ BACKER ROD, TYP.

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

113

**DETAIL PLAN: PROJECTED CURTAINWALL AT BRICK W/ CMU WALL**

SCALE: 3"=1'-0"

61-8102-01 C



**DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS**

DRAWING NO.

113

DATE

11/1/2019