



CMU

APPLY DOWSIL™ 778 SILICONE LIQUID FLASHING AT HEAD AND 4" ONTO FACE OF SHEETING OR DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING

STUCCO COATING

GRADE D BUILDING PAPER (60 MINUTE PAPER)

MECHANICALLY FASTENED METAL LATH

STUCCO WEEP CREED

TRIM

CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT WITH BACKER ROD AS AIR SEAL BETWEEN WINDOW FRAME AND DOWSIL™ 778 SILICONE LIQUID FLASHING

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

210

DETAIL SECTION: STOREFRONT HEAD AT STUCCO ON MASONRY WALL

SCALE: 3"=1'-0"

61-8118-01 C



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.	210
DATE	11/1/2019