



LIGHT GAGE STUD WALL W/ INSULATION BY OTHER

STUCCO COATING

GRADE D BUILDING PAPER (60 MINUTE PAPER)

MECHANICALLY FASTENED METAL LATH

DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING LAPPED OVER FLASHING MEMBRANE MIN. 1"

APPLY DOWSIL™ 778 SILICONE LIQUID FLASHING AT HEAD AND 4" ONTO FACE OF SHEETING OR DEFENDAIR™ 200C AIR AND WEATHER BARRIER COATING

STUCCO WEEP SCREED

TRIM

CONTINUOUS BEAD OF DOWSIL™ 791 SILICONE WEATHERPROOFING SEALANT WITH BACKER ROD AS AIR SEAL BETWEEN WINDOW FRAME AND DOWSIL™ 778 SILICONE LIQUID FLASHING

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

220

**DETAIL SECTION: STOREFRONT HEAD AT STUCCO ON LIGHT GAGE STUD WALL**

SCALE: 3"=1'-0"

61-8122-01 C



**DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS**

DRAWING NO.  
DATE

220

11/1/2019