



CMU/CONCRETE

STUCCO

APPLY DOWSIL™ 778 SILICONE LIQUID FLASHING
AT HEAD AND ONTO FACE OF CMU/ CONCRETE

EXTERNAL CORNER REINFORCEMENT
INSTALLED PER ASTM C1063 OR C1787

CONTINUOUS BEAD OF DOWSIL™ 790
SILICONE BUILDING SEALANT

ANY COMMENTS, MARK-UP TO DESIGN DETAILS, OR ILLUSTRATIONS ARE PROVIDED TO SUGGEST HOW DOW SILICONES' BUILD A BETTER BARRIER PRODUCTS MAY BE INCORPORATED INTO A PROJECT. DOW SILICONES DOES NOT OFFER DESIGN SERVICES. ALL INFORMATION AND ILLUSTRATIONS ARE PROVIDED ON AN "AS-IS" BASIS WITHOUT ANY WARRANTY WHATSOEVER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

310

**DETAIL SECTION: STOREFRONT/WINDOW/ CURTAIN WALL
HEAD AT DIRECT APPLIED STUCCO TO MASONRY/ CONC. WALL**

SCALE: 3"=1'-0"

61-8129-01 A



DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS

DRAWING NO.
DATE

310

11/1/2019