



CONTINUOUS BEAD OF  
DOWSIL™ 790 SILICONE BUILDING  
SEALANT

EXTERNAL CORNER  
REINFORCEMENT INSTALLED PER  
ASTM C1063 OR C1787

APPLY DOWSIL™ 778 SILICONE LIQUID  
FLASHING AT SILL AND ONTO FACE OF  
CMU/ CONCRETE

STUCCO

ANY COMMENTS, MARK-UP TO DESIGN  
DETAILS, OR ILLUSTRATIONS ARE PROVIDED  
TO SUGGEST HOW DOW SILICONES' BUILD A  
BETTER BARRIER PRODUCTS MAY BE  
INCORPORATED INTO A PROJECT. DOW  
SILICONES DOES NOT OFFER DESIGN  
SERVICES. ALL INFORMATION AND  
ILLUSTRATIONS ARE PROVIDED ON AN  
"AS-IS" BASIS WITHOUT ANY WARRANTY  
WHATSOEVER, INCLUDING ANY IMPLIED  
WARRANTIES OF MERCHANTABILITY OR  
FITNESS FOR A PARTICULAR PURPOSE.

311

DETAIL SECTION: STOREFRONT/ WINDOW/ CURTAIN WALL  
SILL AT DIRECT APPLIED STUCCO ON MASONRY/ CONC. WALL

SCALE: 3"=1'-0"

61-8130-01 A



**DOWSIL™ AIR AND WEATHER BARRIER SYSTEMS**

DRAWING NO.	311
DATE	11/1/2019