



Technical Data Sheet

DOWSIL™ 9-1350 Silicone Sealant

Fast-cure sealant for automated glazing applications

Features & Benefits

- High green strength
- Fast cure
- Superior unprimed adhesion to wood, vinyl, fiberglass, anodized aluminum and glass window components
- One-part, neutral cure formulation
- Excellent weather resistance against sunlight, rain, snow and temperature extremes
- Low VOC (13 g/L)
- Low shrink
- AAMA certified

Composition

- One-part, neutral-cure RTV silicone sealant

Applications

- The fast-cure nature of DOWSIL™ 9-1350 Silicone Sealant makes it ideally suited for automated glazing systems, resulting in improved throughput and production. Besides its primary use as a back-bedding sealant, this sealant can also be used in cap, toe and heel bead applications.

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

Test ¹	Property	Unit	Result
Uncured²			
CTM 0044	Specific Gravity		1.40
ASTM C 603	Extrusion Rate	grams/minute	180–220
ASTM D 2202	Flow/Sag (Slump)	inch (mm)	< 0.2 (< 5.2)
CTM 0098	Working (Skin-Over) Time	minutes	4–8
ASTM D 2377	Tack-free Time	minutes	5–9

1. CTMs (Corporate Test Methods) correspond to standard ASTM tests in most instances. Copies of CTMs are available upon request.
ASTM: American Society for Testing and Materials
2. Uncured typical properties as produced and tested at manufacturing plants.

Typical Properties (Cont.)

Test	Property	Unit	Result
As Cured — After 7 days at 24°C (75°F) and 50% RH			
ASTM C 661	Durometer, Shore A	points	35
ASTM D 412	Tensile Strength	psi (kg/mm ²)	240 (0.169)
ASTM D 412	Elongation	percent	350
ASTM D 412	Modulus, 100 Percent	psi (kg/mm ²)	120 (0.084)
ASTM D 719	Movement Capability	percent	±25
ASTM C 711	Temperature Range	°C	-40 to 149
		°F	-40 to 300
ASTM C 793	UV Resistance, QUV		Excellent

Description

DOWSIL™ 9-1350 Silicone Sealant is a one-part, neutral-cure RTV sealant formulated to meet the demanding requirements of a back-bedding sealant for the high-speed manufacturing of windows and doors. Specially formulated to quickly develop high green strength, DOWSIL™ 9-1350 Silicone Sealant can increase throughput and productivity with faster unit handling.

DOWSIL™ 9-1350 Silicone Sealant is available in white, gray and black.

Approvals/ Specifications

- AAMA 802.3-92 (Type I & II)
- ASTM C 920, Type S, Grade NS, Class 25, Use NT, A and G

How to Use

Preparation

Surface should be clean and dry before sealant application.

Application

Material can be applied from drums using standard one-component pumping and dispensing equipment.

Handling Precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life and Storage

DOWSIL™ 9-1350 Silicone Sealant should be stored in a dry location below 32°C (90°F). When stored in original, unopened containers, DOWSIL™ 9-1350 Silicone Sealant has a shelf life of 9 months from date of manufacture. Refer to product packaging for “Use By” date.

Packaging Information

DOWSIL™ 9-1350 Silicone Sealant is available in cartridges and drums.

Limitations

DOWSIL™ 9-1350 Silicone Sealant is not intended for use:

- In spaces totally confined from atmospheric moisture during cure
- In continuous water immersion
- In below-grade applications
- In structural glazing applications
- As an insulating glass (IG) sealant
- On surfaces that will require painting or staining
- On surfaces that might bleed oils, plasticizers or solvents
- On frost-laden or wet surfaces
- In areas where abrasion or physical abuse are encountered
- When movement capability greater than 25 percent is required

Premature movement of the unit may affect system performance.

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health and Environmental Information

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, dow.com, or consult your local Dow representative.

Disposal Considerations

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Technical Representative for more information.

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

